

SIDOOR NT40 SWITCHING POWER SUPPLY, INPUT VOLTAGE: 230VAC (+- 15%), 50/ 60 HZ, OUTPUT VOLTAGE: 36VDC, IP54, INCL. AC POWER LINE WITH SCHUKO PLUG (CEE 7/4) LENGTH 2M, INCL. CONNECTING LINE TO THE CONTROL UNIT WITH A LENGTH OF 1,5M, -20 BIS +55 DEGREE CELSIUS



Figure similar

General information	
Product brand name	SIDOOR
Product designation	Switched-mode power supply
Product version	NT40
Installation type/mounting	
Mounting type	Four 5 mm screws
Supply voltage	
Supply voltage (AC)	230 V
relative symmetrical tolerance of the supply voltage	15 %
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Input current	
Current consumption for 2 s, max.	3.5 A
Rated value at 230 V AC	0.7 A
Operational current of fuse protection at input, min.	6 A

Operational current of fuse protection at input, max.	10 A
Tripping characteristic class of fuse protection at input	B
Output voltage	
Rated value (DC)	36 V; SELV
Relative symmetrical tolerance of the output voltage	3 %
Output current	
Rated value, min.	0 A
Rated value, max.	2.5 A
Temporary overload current (for 2 s maximum)	15 A
Power	
Active power input, max.	100 W
Active apparent power, max.	650 V·A
Emitted active power, max.	100 W
Emitted active power (restricted to 2 s)	540 W
Efficiency at 230 V AC (with 100 W emitted active power)	90 %
Isolation	
Overvoltage category	2
Degree and class of protection	
IP degree of protection	IP54
Equipment protection class	I
Standards, approvals, certificates	
CE mark	Yes
EAC (formerly Gost-R)	Yes
TÜV Inspectorate approval	Yes
Standard for EMC	EMC Directive 2004/108/EC, EN 12015, EN 12016
Standard for safety	EN 60950-1:2006
Ambient conditions	
Ambient temperature during operation	
• min.	-20 °C
• max.	55 °C
• Remark	No direct exposure to the sun
Ambient temperature during storage/transportation	
• Storage, min.	-20 °C
• Storage, max.	70 °C
• Transportation, min.	-40 °C
• Transportation, max.	70 °C
Air pressure acc. to IEC 60068-2-13	
• Installation altitude above sea level, max.	2 000 m

Relative humidity	
• No condensation, min.	10 %
• No condensation, max.	93 %
Cables	
Cable length	
• Input side	2 m
• Output side	1.5 m
Connection method	
Design of electrical connection at input	SCHUKO connector DIN 49.441, CEE7/VII
Design of electrical connection at output	WAGO 721-103/026
Dimensions	
Width	270 mm
Height	55 mm
Depth	80 mm
last modified:	10/28/2016