

AUXILIARY SWITCH ATTACHABLE F. RES.CURRENT OP.CIRC.  
BREAKER F. 100+125A, 1NO+1NC



| Model                                    |                                           |
|------------------------------------------|-------------------------------------------|
| product brandname                        | SENTRON                                   |
| Product designation                      | Auxiliary current switch                  |
| Design of the product                    | Mountable                                 |
| Design of the product / factory mounted  | No                                        |
| Switching capacity                       |                                           |
| Switching capacity current / Rated value | 5 A                                       |
| Main circuit                             |                                           |
| Operating voltage / rated value          | 230 V                                     |
| Control current                          |                                           |
| Type of voltage / of control voltage     | AC/DC                                     |
| Product details                          |                                           |
| Product extension                        | Auxiliary current switch                  |
| • can be mounted                         | residual current operated circuit breaker |
| Number                                   |                                           |
| Number of fault signal contacts          | 0                                         |
| Number of NC contacts                    | 1                                         |

|                       |   |
|-----------------------|---|
| Number of NO contacts | 1 |
| Number of CO contacts | 0 |

#### Mechanical Design

|                       |       |
|-----------------------|-------|
| Height                | 87 mm |
| Width                 | 9 mm  |
| Depth                 | 60 mm |
| Number of width units | 0.5   |
| Net weight            | 61 g  |

#### General Product Approval



#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SW3330>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SW3330/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SW3330](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SW3330)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>

