

SIMATIC S7-1500, FRONTCONNECTOR PUSH-IN TYPE; 40PIN, FOR 25MM WIDE S7-1500 MODULES AND COMPACT CPU, INCL. CABLE STRAP



Connection method	
Connection I/O signals	
• Connection method • Number of lines per connection	Push-in terminal 1; or max. 8x 2 conductors to 1.5 mm² (in total) in a shared end sleeve and max. 32x 0.75 mm² single core
Conductor cross-section in mm²	
— Connectable cable cross-sections for massive cables, min.	0.25 mm²
— Connectable cable cross-sections for massive cables, min.	1.5 mm²; max. 32x 0.75 mm², 8x 1.5 mm²
— Connectable cable cross-sections for flexible cables without end sleeve, min.	0.25 mm²
— Connectable cable cross-sections for flexible cables without end sleeve, max.	1.5 mm²; max. 32x 0.75 mm², 8x 1.5 mm²
— Connectable cable cross-sections for flexible cables with end sleeve, min.	0.25 mm²
— Connectable cable cross-sections for flexible cables with end sleeve, max.	1.5 mm²; max. 32x 0.75 mm², 8x 1.5 mm²
Conductor cross-section acc. to AWG	

— Connectable cable cross-sections for massive cables, min.	24
— Connectable cable cross-sections for massive cables, min.	16; max. 32x AWG 19, 8x AWG 16
— Connectable cable cross-sections for flexible cables without end sleeve, min.	24
— Connectable cable cross-sections for flexible cables without end sleeve, max.	16; max. 32x AWG 19, 8x AWG 16
— Connectable cable cross-sections for flexible cables with end sleeve, min.	24
— Connectable cable cross-sections for flexible cables with end sleeve, max.	16; max. 32x AWG 19, 8x AWG 16
Wire end processing	
— Stripped length of cables, min.	8 mm
— Stripped length of cables, max.	11 mm
— End sleeve acc. to DIN 46228 without plastic sleeve	Form A, 10 mm long
— End sleeve acc. to DIN 46228 with plastic sleeve	Form E, 8 mm and 10 mm long
Mounting	
— Tool	Screwdriver, conical design, 3 mm to 3.5 mm
Dimensions	
Width	25.5 mm
Height	131 mm
Depth	37 mm
Weights	
Weight, approx.	123 g
last modified:	10/28/2016