

Product type designation



SIPLUS NET CP 343-1

SIPLUS NET CP343-1 -25 ... +70 DEGREES C WITH CONFORMAL COATING BASED ON 6GK7343-1EX30-0XE0 . COMMUNIKATIONS PROCESSOR FOR CONNECTING SIMATIC S7-300 TO IND. ETHERNET VIA ISO AND TCP/IP, PROFINET IO-CONTROLLER OR PROFINET IO-DEVICE, INTEGR. 2-PORT SWITCH ERTEC200 S7-COMM., FETCH/WRITE, SEND/RCV W. AND W/O RFC1006,MULTICAST DHCP, NTC-CPU SYNC, DIAGNOSTIC, INITIALIZATION VIA LAN, 2 X RJ45 CONNECT. FOR LAN WITH 10/100 MBIT/S

Transmission rate

Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

2

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet
- for power supply

2

1

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet
- of Industrial Ethernet interface
- for power supply

RJ45 port

RJ45 port

2-pole plugable terminal block

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Supply voltage

24 V

Supply voltage / external

24 V

Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	15 %
Consumed current	
• from backplane bus / at DC / at 5 V / typical	0.2 A
• from external supply voltage / at DC / at 24 V / typical	0.16 A
• from external supply voltage / at DC / at 24 V / maximum	0.2 A
Power loss [W]	5.8 W

Permitted ambient conditions

Ambient temperature	
• during operation	-25 ... +70 °C
• for horizontally arranged busbars / during operation	-25 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Ambient condition / relating to ambient temperature - air pressure - installation altitude	-25 ... +70°C at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // -25 ... +60°C at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // -25 ... +50°C at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity / with condensation / maximum	100 %; r.F., incl. condensation/frost permitted (no commissioning in bedewed state)
Resistance to biologically active substances	
• conformity acc. to EN 60721-3-3	Yes; Compliance with EN 60721-3-3, Class 3B2 mold, fungus, and sponge spores (except fauna). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to chemically active substances	
• conformity acc. to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to mechanically active substances	
• conformity acc. to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation!
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-300 single width
Width	40 mm
Height	125 mm
Depth	120 mm
Net weight	0.22 kg

Performance data / open communication

Number of Multicast stations	16
------------------------------	----

Performance data / S7 communication

Number of possible connections / for S7 communication	
• maximum	16
Performance data / multi-protocol mode	
Number of active connections / with multi-protocol mode	32
Performance data / PROFINET communication / as PN IO-Controller	
Number of external PN IO lines / with PROFINET / per rack	1
Amount of data	
• as user data for input variables / as PROFINET IO controller / maximum	1 Kibyte
• as user data for input variables / as PROFINET IO controller / maximum	1 Kibyte
• as user data for input variables per PN IO device / as PROFINET IO controller / maximum	240 byte
• as user data for output variables per PN IO device / as PROFINET IO controller / maximum	240 byte
Performance data / PROFINET communication / as PN IO-Device	
Amount of data	
• as user data for input variables / as PROFINET IO device / maximum	512 byte
• as user data for input variables / as PROFINET IO device / maximum	512 byte
• as user data for input variables / for each sub-module as PROFINET IO device	240 byte
• as user data for input variables / for each sub-module as PROFINET IO device	240 byte
• as user data for the consistency area for each sub-module	240 byte
Number of submodules / per PROFINET IO-Device	32
Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• DCP	Yes
• LLDP	Yes
Configuration software	
• required	STEP 7 V5.4 SP2 or higher
Product functions / switch	
Product feature / Switch	Yes
Product function	
• with IRT / PROFINET IO switch	Yes

- Configuration with STEP 7

Yes

Product functions / Redundancy

Product function	
• Ring redundancy	Yes
• Redundancy manager	No
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes

Product functions / Security

Product function	
• ACL - IP-based	Yes
• ACL - IP-based for PLC/routing	No
• switch-off of non-required services	Yes

Product functions / Time

Product function / SICLOCK support	Yes
Protocol / is supported	
• NTP	Yes

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
----------------------	--

last modified:

10/26/2016