

SIMATIC IFP2200 FLAT PANEL 22" DISPLAY (16:9), W/O TOUCH, DISPLAY ONLY STANDARD VERSION, MAX 5M, 1920X1080 PIXEL, FOR 24V DC, DISPLAYPORT / DVI INTERFACE INCL. DVI-CABLE 1,8M



Figure similar

General information	
Product type designation	IFP2200
Short designation	Flat Panel 22" display
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	21.5 in
Screen diagonal (cm)	56 cm
Display width	476 mm
Display height	268 mm
Viewing angle	170° x 170°
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216
Number of colors (bit levels)	24 bit
Resolution (pixels)	
• Resolution (WxH in pixel)	1920 x 1080
• Horizontal image resolution	1 920 Pixel
• Vertical image resolution	1 080 Pixel

• Pixel size, horizontal	0.2475 mm
• Pixel size, vertical	0.2475 mm
General features	
• Detachable from computer unit	5 m
• Brightness/contrast	250 cd/m ² / 1000:1
• non-reflective and tempered mineral glass screen	Yes
• Luminance	250 cd/m ²
Backlighting	
• Type of backlighting	LED
• MTBF backlighting (up to 50%, at 25 °C)	50 000 h; At 25°C
• Backlight dimmable	Yes; 0-100 %
Control elements	
Keyboard fonts	
• Function keys	No
Installation type/mounting	
Built-in unit	Yes; Portrait mode possible
• permissible angle to the vertical backward (console)	35°
• permissible angle to the vertical forward (ceiling mounting)	35°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Power loss	
Power loss DC	
• Typical	40 W
• Maximum	65 W
Interfaces	
Video interfaces	
• DVI-D	Yes
• DisplayPort	Yes; DisplayPort V1.1
Touch interfaces	
• USB	No
Degree and class of protection	
IP65 at front	Yes
Enclosure Type 4 at the front	Yes
NEMA4 at the front	No

NEMA4X at the front	No
IP20 rear	Yes
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes; Corresponds to UL 508
RCM (formerly C-TICK)	Yes
KC approval	Yes
Use in hazardous areas	
• FM Class I Division 2	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	45 °C; Vertical installation (horizontal)
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	95 %; Non-condensing
Vibrations	
• Vibration load in operation	1 gn
• Vibration load during transport/storage	1 gn
Shock testing	
• Shock load during operation	15 gn
• Shock load during transport/storage	15 gn
Mechanics/material	
Type of housing (front)	aluminum
Enclosure material (front)	
• Aluminum	Yes
Dimensions	
Width of the housing front	560 mm
Height of housing front	380 mm
Mounting cutout, width	542 mm; Tolerance: +1 mm
Mounting cutout, height	362 mm; Tolerance: +1 mm
Overall depth	62.5 mm
Weights	
Weight without packaging	6.5 kg
Weight incl. packaging	7.6 kg
last modified:	10/25/2016