

SIMATIC ET 200SP, ANALOG INPUT MODULE, AI 2X U/I 2-,4-WIRE HIGH FEAT., FITS TO BU-TYPE A0, A1, COLOR CODE CC05, CHANNEL DIAGNOSIS, 16BIT, +/-0,1%



General information	
Product type designation	ET 200SP, AI 2x U/I 2-/4-wire High Feature, PU 1
Firmware version	V2.0
• FW update possible	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC03
Product function	
• I&M data	Yes; I&M0 to I&M3
• Measuring range scalable	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated as of version	V13
• STEP 7 configurable/integrated as of version	V5.5 / -
• PCS 7 configurable/integrated as of version	V8.1 SP1
• PROFIBUS as of GSD version/GSD revision	GSD Revision 5
• PROFINET as of GSD version/GSD revision	GSDML V2.3
Operating mode	
• Oversampling	No

- MSI

Yes

CiR – Configuration in RUN

Reparameterization possible in RUN

Yes

Calibration possible in RUN

Yes

Supply voltage

Rated value (DC)

24 V

permissible range, lower limit (DC)

19.2 V

permissible range, upper limit (DC)

28.8 V

Reverse polarity protection

Yes

Input current

Current consumption (rated value)

39 mA; without sensor supply

Encoder supply

24 V encoder supply

- 24 V

Yes

- Short-circuit protection

Yes

- Output current, max.

20 mA; max. 50 mA per channel for a duration < 10 s (two-wire)

Additional 24 V encoder supply

- Short-circuit protection

Yes; channel by channel

- Output current, max.

100 mA; max. 150 mA for a duration of < 10 s (four-wire)

Power loss

Power loss, typ.

0.95 W; without sensor supply

Address area

Address space per module

- Address space per module, max.

4 byte; + 4 byte for scaling of measured values, + 1 byte for QI information

Hardware configuration

Selection of BaseUnit for connection variants

- 2-wire connection

BU type A0, A1

- 4-wire connection

BU type A0, A1

Analog inputs

Number of analog inputs

2; Differential inputs

permissible input voltage for voltage input (destruction limit), max.

30 V

permissible input current for current input (destruction limit), max.

50 mA

Analog input with oversampling

No

Standardization of measured values

Yes

Input ranges (rated values), voltages

- 0 to +10 V

Yes; 15 bit

- Input resistance (0 to 10 V)

75 kΩ

• 1 V to 5 V • Input resistance (1 V to 5 V) • -10 V to +10 V • Input resistance (-10 V to +10 V) • -5 V to +5 V • Input resistance (-5 V to +5 V)	Yes; 15 bit 75 k Ω Yes; 16 bit incl. sign 75 k Ω Yes; 16 bit incl. sign 75 k Ω
Input ranges (rated values), currents	
• 0 to 20 mA • Input resistance (0 to 20 mA) • -20 mA to +20 mA • Input resistance (-20 mA to +20 mA) • 4 mA to 20 mA • Input resistance (4 mA to 20 mA)	Yes; 15 bit 130 Ω Yes; 16 bit incl. sign 130 Ω Yes; 15 bit 130 Ω
Cable length	
• shielded, max.	1 000 m; 200 m for voltage measurement
Analog value generation for the inputs	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max. • Integration time, parameterizable • Interference voltage suppression for interference frequency f1 in Hz • Basic execution time of the module (all channels released)	16 bit Yes 16.6 / 50 / 60 / 300 / 600 / 1 200 / 2 400 / 4 800 1 ms
Smoothing of measured values	
• Number of smoothing levels • parameterizable	6; none; 2-/4-/8-/16-/32-fold Yes
Encoder	
Connection of signal encoders	
• for voltage measurement • for current measurement as 2-wire transducer — Burden of 2-wire transmitter, max. • for current measurement as 4-wire transducer	Yes Yes 650 Ω Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.003 %/K
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.01 %
Operational error limit in overall temperature range	

• Voltage, relative to input range, (+/-)	0.1 %
• Current, relative to input range, (+/-)	0.1 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.05 %; 0.1 % at SFU 4.8 kHz
• Current, relative to input range, (+/-)	0.05 %; 0.1 % at SFU 4.8 kHz
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
• Common mode voltage, max.	35 V
• Common mode interference, min.	90 dB

Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Filtering and processing time (TCI), min.	800 µs
Bus cycle time (TDP), min.	1 ms
Jitter, max.	5 µs

Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Limit value alarm	Yes; two upper and two lower limit values in each case
Diagnostic messages	
• Monitoring the supply voltage	Yes
• Wire-break	Yes; Measuring range 4 to 20 mA only
• Short-circuit	Yes; channel-by-channel, at 1 to 5 V or for short-circuit in encoder supply
• Group error	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; Green LED
• for channel diagnostics	Yes; Red LED
• for module diagnostics	Yes; green/red DIAG LED

Potential separation	
Potential separation channels	
• between the channels	Yes
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes

Permissible potential difference	
between the inputs (UCM)	75 V DC/60 V AC

Isolation	
Isolation tested with	707 V DC (type test)

Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	32 g
last modified:	10/28/2016