

Data sheet

6XV1875-5DE30

Product type designation

Product description

SIMATIC NET Antenna Connection Cable RSMA/SMA Male/ Male

Connecting cable for SIMATIC NET antennas, preassembled
SIMATIC NET, IWLAN R-SMA/SMA MALE/MALE FLEXIBLE
CONNECTION CABLE PREASSEMBLED, LENGTH 0.30M
FLEXIBLE CONNECTION CABLE FOR COMPONENTS WITH R-
SMA AND SMA CONNECTION



Suitability for use

Flexible connecting cable for connecting a cabinet bushing with
SMA connection to an access point/client

Wire length

0.3 m

Electrical data

Number of electrical connections

2

Type of electrical connection

RSMA/ SMA male/male

Transmission frequency

0 ... 6000 MHz

Damping ratio per length

- at 2.4 GHz / typical
- at 5.2 GHz / typical
- at 5.85 GHz / typical

0.53 dB/m

0.83 dB/m

0.89 dB/m

Return loss / minimum

23 dB

Impedance

- Rated value

50 Ω

Capacity per length / at 1 kHz

82 pF/m

Relative speed

82 %

Mechanical data

Design of the shield	Braided shield made of tin-plated copper wires
Outer diameter	
• of inner conductor	1.4 mm
• of dielectric	3.8 mm
• of cable sheath	6.3 mm
Symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
Thickness / of cable sheath	0.76 mm
Material	
• of inner conductor	Cu
• of dielectric	polyethylene foam
• of cable sheath	FRNC
Color	
• of cable sheath	pastel turquoise
Bending radius	
• with single bend / minimum permissible	32 mm
• with multiple bends / minimum permissible	45 mm
Tensile load / maximum	80 N
Weight per length	75 kg/km

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +80 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
• during installation	-25 ... +80 °C
Chemical resistance	
• to mineral oil	conditional resistance
Radiological resistance / to UV radiation	resistant
Protection class IP	IP68; when plugged in

Product properties, functions, components / general

Product feature	
• halogen-free	Yes
• silicon-free	Yes

Standards, specifications, approvals

Certificate of suitability	
• RoHS conformity	Yes
• Fire protection in accordance with EN 45545-2	No
Standard	
• for behavior in fire: flame resistance	UL 1685 (Vertical tray), UL 1581 Sec. 1090 (H)

Further Information / Internet Links

Internet-Link	
---------------	--

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

last modified:

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

10/12/2016