

SIMATIC HMI KP8F PN, KEY PANEL, 8 SHORT-STROKE KEYS WITH MULTI-COLOR LED'S, PROFINET INTERFACE WITH PROFISAFE, 8 DI/DO AND 2 SAFETY DI PINS, 24V DC LOOP THROUGH CONFIGURABLE WITH STEP7 V5.5 AND LATER



General information	
Product type designation	SIMATIC HMI KP8F PN
Control elements	
With parameterizable keys	Yes
Keyboard fonts	
- Membrane keyboard — user-definable label membrane keys - Short-stroke keys — Number of short-stroke keys	Yes 8
Expansions for operator control of the process	
- DP direct LEDs (LEDs as S7 output I/O) - Number of color modes for LED - Direct keys (keys as S7 input I/O)	8; Adjustable brightness 5; Red, green, blue, yellow, white 8
Installation type/mounting	
Mounting position	vertical
Rack mounting possible	No
Front installation possible	Yes; Compatible with extension unit dimensions
Rail mounting possible	No

Wall mounting/direct mounting possible	No
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	30°; To the front/rear
Mounting technology	Mounting clip
Number of slots for command devices and signaling units	0

Supply voltage

Type of supply voltage	DC
Rated value (DC)	24 V; 24 V can be looped through connector, interrupted when pulled
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Input current

Current consumption (rated value)	0.3 A
-----------------------------------	-------

Type of output

LED colors	
• red	Yes
• yellow	Yes
• green	Yes
• white	Yes
• blue	Yes

Digital inputs

Number of digital inputs	8; Total inputs and outputs max. 8 and 1x SIL 2 or 2x SIL 3
Input voltage	
• Rated value (DC)	24 V

Digital outputs

Number of digital outputs	8; Max. 8 inputs and outputs (total)
Short-circuit protection	Yes
Switching capacity of the outputs	
• with resistive load, max.	100 mA
Output voltage	
• Rated value (DC)	24 V; Non-isolated
Total current of the outputs	
• Current per channel, max.	100 mA
• Current per group, max.	800 mA

Interfaces

Number of industrial Ethernet interfaces	2; For the construction of lines and rings without external switch
Number of PROFINET interfaces	2; Incl. switch
Industrial Ethernet	

- Industrial Ethernet status LED 2; Per port
- Number of ports of the integrated switch 2; Per port

Protocols

PROFINET	Yes; also 3rd party PLC
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
IRT	Yes
MRP	Yes
PROFIsafe	Yes; 1x SIL 2 (two-channel) or 2x SIL 3 (single-channel) emergency stop sensor
PROFIBUS	No
MPI	No
AS-Interface	No
EIB/KNX	No

Protocols (Ethernet)

- TCP/IP No

Further protocols

- AS-Interface Safety at Work No
- CAN No
- Data-Highway No
- DeviceNet No
- DeviceNet Safety No
- EtherNet/IP No
- Foundation Fieldbus No
- INTERBUS No
- INTERBUS-Safety No
- Local Operating Network No
- MODBUS No
- SafetyBUS p No
- SERCOS No
- SUCOnet No
- other bus systems No

Test commissioning functions

Illuminant test	Yes; During switch on
Key and signal lamp test	Yes; Automatically when switching on

EMC

Emission of radio interference acc. to EN 55 011

- Limit class A, for use in industrial areas Yes; Group 1, measured at a distance of 10 m
- Limit class B, for use in residential areas No

Degree and class of protection

IP (at the front)	IP65
-------------------	------

Enclosure Type 4 at the front	No
Enclosure Type 4x at the front	Yes; Incl. NEMA12
IP (rear)	IP20

Standards, approvals, certificates

CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Suitable for safety functions	Yes

Marine approval

• Germanischer Lloyd (GL)	No
• American Bureau of Shipping (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (Class NK)	No
• Polski Rejestr Statkow (PRS)	No

Use in hazardous areas

• ATEX Zone 2	Yes
• ATEX Zone 22	Yes
• cULus Class I Zone 1	No
• cULus Class I Zone 2, Division 2	Yes
• FM Class I Division 2	Yes

Ambient conditions

Ambient temperature during operation

• min.	0 °C
• max.	55 °C
• Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	55 °C
• Operation (max. tilt angle)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, min.	45 °C
• Operation (vertical installation, portrait format)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	45 °C
• Operation (max. tilt angle, portrait format)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, min.	45 °C

Ambient temperature during storage/transportation

• min.	-20 °C
--------	--------

• max.	60 °C
Relative humidity	
• Operation, max.	95 %; no condensation
Configuration	
Configuration software	
• STEP 7 Basic (TIA Portal)	Yes
• STEP 7 Professional (TIA Portal)	Yes
Functionality under WinCC (TIA Portal)	
Process coupling	
• S7-1200	Yes; with ET 200pro CPU and ET 200S CPU
• S7-1500	Yes
• S7-200	No
• S7-300/400	Yes; with F-CPU: STEP 7 V11 SP1 (or higher) and Safety V11 (or higher) or SIMATIC STEP 7 Basic V11 (or higher)
• LOGO!	No
• WinAC	Yes
• SINUMERIK	No
• SIMOTION	No
• Allen Bradley (EtherNet/IP)	No
• Allen Bradley (DF1)	No
• Mitsubishi (MC TCP/IP)	No
• Mitsubishi (FX)	No
• OMRON (FINS TCP)	No
• OMRON (LINK/Multilink)	No
• Modicon (Modbus TCP/IP)	No
• Modicon (Modbus)	No
Mechanics/material	
Enclosure material (front)	
• Plastic	Yes
• Aluminum	No
• Stainless steel	No
Service life	
• Short-stroke keys (in switching cycles)	1 500 000
• LEDs (ON period)	100 %
Dimensions	
Width of the housing front	98 mm
Height of housing front	155 mm
Mounting cutout, width	68 mm; Max. thickness of mounting plate 2 - 6 mm
Mounting cutout, height	129 mm
Overall depth	49 mm; Incl. angled SIMATIC Ethernet connector

Weights

Weight without packaging

280 g

last modified:

10/28/2016