

OUTPUT COUPLING 24 V DC !!! PHASE-OUT PRODUCT !!! FOR
FURTHER INFORMATION PLEASE CONTACT OUR SALES
STAFF! HL - OUTPUT, 3 A, 30 VDC SHORT-CIRC.-PROOF, CAGE
CLAMP HOUSING WIDTH 6.2 MM



Figure similar

General technical data:	
Type of voltage	DC
Control supply voltage	
• at DC rated value	
— minimum	
— maximum	24 V
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	1
Number of CO contacts for auxiliary contacts	0
Switching behavior	monostable
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	K
Mechanical data:	
Type of electrical connection	spring-loaded terminals
Type of electrical connection Plug-in socket	No
Design of the relay operating mechanism	poled

Design of the switching function positively driven	No
Product component Plug-in socket	No
Width	6.2 mm
Height	80 mm
Depth	86 mm

Ambient conditions:

Protection class IP	IP20
Ambient temperature during operation	-25 ... +60 °C

Certificates/ approvals:

General Product Approval			Declaration of Conformity	Test Certificates	other
 CCC	 UL	 EAC	 EG-Konf.	spezielle Prüfbescheinigungen n	sonstig

other

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7005-3PB74>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7005-3PB74>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7005-3PB74&lang=en



last modified:

10/07/2016