

MINIATURE POWER RELAY SCREW TERMINALS, 3NO+1NC
SNAP-ON MOUNTING ON STANDARD MOUNTING RAIL AC
OPERATION AC 110V 50HZ/AC 132V 60HZ



Control circuit/ Control:	
Control version of the switch operating mechanism	conventional
Type of voltage of the control supply voltage	AC
Control supply voltage frequency	
• 1 rated value	50 Hz
• 2 rated value	60 Hz
Control supply voltage	
• at AC	
— at 50 Hz	
— rated value	110 V
— at 60 Hz	
— rated value	132 V
Number of NC contacts for auxiliary contacts	
• lagging switching	0
• instantaneous contact	0
Number of NO contacts for auxiliary contacts	
• leading contact	0
• instantaneous contact	0
Auxiliary circuit:	
Number of NC contacts for auxiliary contacts	0
Type of electrical connection for main current circuit	screw-type terminals
Type of electrical connection for auxiliary and control current circuit	screw-type terminals
Mechanical data:	
Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Mounting type Side-by-side mounting	Yes
Width	45 mm
Height	48 mm
Depth	68 mm
Certificates/ approvals:	

General Product Approval			Declaration of Conformity	Test Certificates	Shipping Approval
				spezielle Prüfbescheinigungen n	
CCC	UL		EG-Konf.		DNV

Shipping Approval			other
			Umweltbestätigung
LRS	PRS	RMRS	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TK2031-0AF0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TK2031-0AF0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TK2031-0AF0&lang=en

last modified:

10/07/2016