

INPUT INTERFACE WITH PLUG-IN !!! PHASE-OUT PRODUCT !!!
FOR FURTHER INFORMATION PLEASE CONTACT OUR SALES
STAFF! REL. 1 CH. CON. HARD GOLD-PLAT. SCREW TERMINAL
24 V DC ENCLOSURE WIDTH 6.2 MM



Figure similar

General technical data:	
Type of voltage	DC
Control supply voltage	
• at DC rated value	
— minimum	
— maximum	24 V
Switching behavior	monostable
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of CO contacts for auxiliary contacts	1
Operating current of auxiliary contacts	
• at DC-13	
— at 24 V	
— at 110 V	
— at 230 V	
• at AC-15	
— at 230 V	

Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	K

Mechanical data:

Type of electrical connection	screw-type terminals
Type of electrical connection Plug-in socket	Yes
Design of the relay operating mechanism	poled
Design of the switching function positively driven	No
Product component Plug-in socket	Yes
Width	6.2 mm
Height	89.5 mm
Depth	92 mm

Ambient conditions:

Protection class IP	IP20
Ambient temperature during operation	-25 ... +55 °C

Certificates/ approvals:

General Product Approval	Declaration of Conformity	Test Certificates	other
 CCC	 UL	 EAC	 EG-Konf.
		spezielle Prüfbescheinigungen n	Bestätigungen

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7014-1BM02>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7014-1BM02>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7014-1BM02&lang=en

last modified:

10/24/2016