

WINDOW-TYPE CURRENT TRANSFORMER, CLASS 1 400A/5A,
5VA PRIMARY CURRENT 400A, 5VA



Figure similar

Model	
Product designation	Window-type current transformers
Protection class	
Protection class IP	IP20
Connections	
Type of electrical connection / at output	screw-type terminals
Mechanical Design	
Height	85.5 mm
Width	64 mm
Width	
• of the push-through bus bar / at 1 bus bar / maximum	30 mm
• of the push-through bus bar / in case of 2 bus bars / maximum	25 mm
Depth	80 mm
Mounting type	screw fixing

Outer diameter / of the push-through conductor / maximum	28 mm
Environmental conditions	
Ambient temperature	
• during operation / minimum	-10 °C
• during operation / maximum	55 °C
Certificates	
Equipment marking / acc. to DIN EN 61346-2	T
General Product Approval	Declaration of Conformity

Further information
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/4NC5225-2CE20
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/4NC5225-2CE20/all
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4NC5225-2CE20
CAX-Online-Generator http://www.siemens.com/cax
Tender specifications http://www.siemens.com/specifications