

Product type designation



SIPLUS SCALANCE X208

SIPLUS NET SCALANCE X208 -40 ... +60 DGR C INCL.
CONFORMAL COATING BASED ON 6GK5208-0BA10-2AA3 .
MANAGED IE SWITCH, 8 X 10/100MBIT/S RJ45 PORTS, LED
DIAGNOSTICS, ERROR SIGNAL CONTACT WITH SET BUTTON,
REDUNDANT POWER SUPPLY, PROFINET-IO DEVICE,
NETWORK MANAGEMENT, INTEGRATED REDUNDANCY
MANAGER, INCL. ELECTRONIC MANUAL ON CD, C-PLUG
OPTIONAL

Figure similar

Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / others	
design of the removable storage	
• C-PLUG	Yes
Signal-Inputs/outputs	
Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.185 A
Permitted ambient conditions	

Ambient temperature	
• during operation	-40 ... +60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity	
• with condensation / maximum	100 %; r.F., incl. condensation/frost permitted (no commissioning in bedewed state)
Ambient condition / relating to ambient temperature - air pressure - installation altitude	-40 ... +60 °C at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // -40 ... +50 °C at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // -40 ... +40 °C at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Resistance to biologically active substances / conformity acc. to EN 60721-3-3	Yes; Compliance with EN 60721-3-3, Class 3B2 mold, fungus, and sponge spores (except fauna). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to chemically active substances / conformity acc. to EN 60721-3-3	Yes; Compliance with EN 60721-3-3, class 3C4 incl. salt spray according to EN 60068-2-52 (severity 3). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to mechanically active substances / conformity acc. to EN 60721-3-3	Yes; Compliance with EN 60721-3-3, Class 3S4 including sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation!
Protection class IP	IP30

Product properties, functions, components / general

Cascading in the case of a redundant ring / at reconfiguration time of ≤ 0.3 s	50
---	----

Product functions / management, configuration

Product function	
• switch-managed	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher-level designation/location designation	Yes

Standards, specifications, approvals

Standard	
• for FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
• for hazardous zone	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Certificate of suitability / CE marking	Yes
Certificate of suitability	EN 61000-6-2, EN 61000-6-4
• Railway application in accordance with EN 50155	No

• Railway application in accordance with EN 50124-1	No
• KC approval	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
• Polski Rejestr Statkow (PRS)	No
MTBF / at 40 °C	83.71 y

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
----------------------	--

last modified:

10/12/2016