

SITOP PSU8600 40A/4X10A PN
SITOP PSU8600 40A/4X 10A PN STABILIZED POWER SUPPLY
INPUT: 3 400-500 V AC OUTPUT: 24 V/40 A/4X 10 A DC WITH
PN/IE CONNECTION



Input	
Input	3-phase AC
Rated voltage value Vin rated	400 ... 500 V
Voltage range AC	320 ... 575 V
• Note	Derating 320 ... 360 and 530 ... 575 V
Wide-range input	Yes
Mains buffering at lout rated, min.	15 ms; at Vin = 400 V; Prioritized supply Output 1 at power failure can be selected via DIP switch
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
• at rated input voltage 400 V	2.75 A
• at rated input voltage 500 V	2.2 A
Switch-on current limiting (+25 °C), max.	14 A
I²t, max.	2.24 A²·s
Built-in incoming fuse	none

Protection in the mains power input (IEC 898)	Required: 3-pole connected miniature circuit breaker 10 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)
---	--

Output	
Output	Controlled, isolated DC voltage
Number of outputs	4
Rated voltage Vout DC	24 V
Output voltage	
• at output 1 at DC Rated value	24 V
• at output 2 at DC Rated value	24 V
• at output 3 at DC Rated value	24 V
• at output 4 at DC Rated value	24 V
Total tolerance, static $\pm$	3 %
Static mains compensation, approx.	0.2 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	100 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	200 mV
Adjustment range	5 ... 28 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer; Derating > 24 V: 4%/V; max. 240 W per output, max. 960 W overall system
Status display	3-color LED for operating state device; LED for operating mode manual/remote; 4 LEDs for communication PROFINET; 3-color LED per output for operating state output; LED green for parallel operation Output 1 and 2 / 3 and 4
Signaling	Relay contact (changeover contact, contact current capacity DC 60 V/0.3 A) for "Operating state OK"
On/off behavior	No overshoot of Vout (soft start)
Startup delay, max.	1 s; Without on-delay of the outputs
connection of outputs operating	Simultaneous connecting-in of all outputs after device booting or delay time of 25 ms, 100 ms or "load-optimized" for sequential cutting-in of the outputs via DIP switches can be set
Voltage increase time of the output voltage maximum	500 ms
Rated current value Iout rated	40 A
Output current	
• per output	10 A
• at output 1 Rated value	10 A
• at output 2 Rated value	10 A
• at output 3 Rated value	10 A
• at output 4 Rated value	10 A
Current range	0 ... 40 A
• Note	+50 ... +60 °C: Derating 2.5%/K; no derating in connection with expansion module CNX8600 and total load of the outputs at the basic device max. 480 W

Supplied active power typical	960 W
Product feature parallel switching of outputs	Yes; Parallel circuit Output 1 with 2 or Output 3 with 4 can be selected via DIP switch
Parallel switching for enhanced performance	No

Efficiency

Efficiency at Vout rated, Iout rated, approx.	93 %
Power loss at Vout rated, Iout rated, approx.	72 W
Power loss [W] during no-load operation maximum	20 W

Closed-loop control

Dynamic mains compensation (Vin rated $\pm 15\%$), max.	0.1 %
Dynamic load smoothing (Iout: 50/100/50 %), Uout $\pm$ typ.	0.4 %
Setting time maximum	10 ms

Protection and monitoring

Output overvoltage protection	< 35 V
Property of the output Short-circuit proof	Yes
Short-circuit protection	electronic overload cut-off; optionally constant current operation can be selected for Output 4 via DIP switches
adjustable response value current of current-dependent overload trip	0.5 ... 10 A
type of threshold value setting	via potentiometer
characteristics of electronic overload switch-off	Ia > 1.0...< 1.5 x Ia threshold permissible for 5 s; Ia limit (= 1.5 x Ia threshold) permissible for 200 ms
characteristics of constant current operation	Ia limit (= 1.5 x Ia threshold) permissible for 5 s, afterwards Ia threshold continuous
Reset	Via sensor per output
Remote reset	Non-electrically isolated 24 V input (signal level "high" at > 15 V)
Overcurrent overload capability in normal operation	Total system overloadable 150% Ia rated to 5 s/min
Overload/short-circuit indicator	3-color LED for operating state device; 3-color LED per output for operating state output

Interface

Specification interface	Ethernet/PROFINET
-------------------------	-------------------

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current • maximum	3.5 mA
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)

Explosion protection	IECEX Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4
FM approval	-
CB approval	Yes
Marine approval	GL; ABS in process
Degree of protection (EN 60529)	IP20

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature	
- during operation — Note - during transport - during storage	-25 ... +60 °C with natural convection -40 ... +85 °C -40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics

Connection technology	Plug-in terminals with screwed connection
Connections	
- Supply input - Output - Auxiliary	L1, L2, L3, PE: Plug-in terminal with 1 screwed connection each for 0.08 ... 4 mm² single-wire / fine stranded 1, 2, 3, 4: Two plug-in terminals (1, 2 and 3, 4) with 2 screwed connections each for 0.2 ... 2.5 mm²; 0 V: Plug-in terminal with 3 screwed connections for 0.5 ... 10 mm² RST (Reset): Plug-in terminal (together with alarm signal) with 1 screwed connection for 0.2 ... 1.5 mm²
Connections signaling contact	11, 12, 14 (alarm signal): Plug-in terminal (together with Reset) with 1 screwed connection each for 0.2 ... 1.5 mm ²
Product function	
- removable terminal at input - removable terminal at output	Yes Yes
Design of the interface for communication	PROFINET/Ethernet: two RJ45 sockets (2-port switch)
Suitability for interaction modular system	Yes
Width of the enclosure	125 mm
Height of the enclosure	125 mm
Depth of the enclosure	150 mm
Required spacing	
- top - bottom - left - right	50 mm 50 mm 0 mm 0 mm

Weight, approx.	2.6 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x15
Electrical accessories	Expansion modules CNX8600, buffer modules BUF8600
Mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
MTBF at 40 °C	226 272 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)