

MOLDED CASE CIRC.BREAKER 3RV1 FOR STARTER
COMBINATION STANDARD SWITCHING CAPACITY RATED
CURRENT IN=400A ELECTRONIC RELEASE SHORT-CIRCUIT
PROTECTION ADJUSTABLE 1-10XLN ICU =120KA AT 400V 3-
POLE, SCREW TERMINAL INCL. PHASE BARRIERS

product brandname	SIRIUS
Product designation	molded-case circuit breaker
Design of the product	for starter combinations

General technical data

Product extension	
• Auxiliary switch	Yes
Surge voltage resistance rated value	8 000 V
Protection class IP	
• on the front	IP20
Shock resistance	12g / 11 ms
Mechanical service life (switching cycles)	
• of the main contacts typical	20 000

Ambient conditions

Installation altitude at height above sea level maximum	2 000 m
Ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C

Main circuit

Number of poles for main current circuit	3
Operating voltage	
• rated value	690 V
• at AC-3 rated value maximum	690 V
Operating current	
• at AC-3	
— at 400 V rated value	400 A
Operating power	
• at AC-3	
— at 400 V rated value	200 kW
Operating frequency	
• at AC-3 maximum	15 1/h

Auxiliary circuit	
Number of CO contacts	
• for auxiliary contacts	0
Protective and monitoring functions	
Maximum short-circuit current breaking capacity (Icu)	
• at AC at 240 V rated value	100 kA
• at AC at 400 V rated value	120 kA
• at AC at 500 V rated value	85 kA
• at AC at 690 V rated value	70 kA
Short-circuit protection	
Design of the overcurrent release and short-circuit release	electronic
Installation/ mounting/ dimensions	
Mounting position	any
Mounting type	screw fixing
Height	205 mm
Width	140 mm
Depth	103.5 mm
Required spacing	
• with side-by-side mounting	
— Backwards	0 mm
— at the side	0 mm
Connections/Terminals	
Product function	
• removable terminal for auxiliary and control circuit	No
Type of electrical connection	
• for main current circuit	screw-type terminals
• for auxiliary and control current circuit	screw-type terminals
Arrangement of electrical connectors for main current circuit	front side
Certificates/approvals	

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
--------------------------	---------------------------	-------------------	-------------------



[spezielle
Prüfbescheinigung](#)
[n](#)



Shipping Approval	other
-------------------	-------



GL



LRS



RINA



RMRS

[sonstig](#)

[Umweltbestätigung](#)

other

[Bestätigungen](#)



VDE

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV1373-7GN10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV1373-7GN10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV1373-7GN10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV1373-7GN10&lang=en

last modified:

10/19/2016