

### Product type designation

### Split Connect Tap

PROFIBUS PA SPLITCONNECT TAP, FOR ASSEMBLING OF PROFIBUS PA SEGMENTS AND CONNECTION OF PA FIELD DEVICES, INSULATION DISPLACEMENT TERMINAL, IP67 PACK.  
UNIT: 10 PIECES = 1 PACK



### Electrical data

|                                  |              |
|----------------------------------|--------------|
| Transfer rate / with PROFIBUS PA | 31.25 kbit/s |
|----------------------------------|--------------|

### Interfaces

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| Number of electrical connections | 3                                           |
| • for PROFIBUS cables            |                                             |
| Type of electrical connection    | integrated insulation displacement contacts |
| • for PROFIBUS cables            |                                             |

### Mechanical data

|                             |                                 |
|-----------------------------|---------------------------------|
| Material / of the enclosure | PBT (polybutyleneterephthalate) |
|-----------------------------|---------------------------------|

### Design, dimensions and weight

|                           |       |
|---------------------------|-------|
| Width                     | 84 mm |
| Height                    | 54 mm |
| Depth                     | 49 mm |
| Net weight                | 170 g |
| Mounting type             | Yes   |
| • 35 mm DIN rail mounting |       |
| • wall mounting           | Yes   |

## Permitted ambient conditions

|                     |                |
|---------------------|----------------|
| Ambient temperature |                |
| • during operation  | -40 ... +85 °C |
| • during storage    | -40 ... +85 °C |
| • during transport  | -40 ... +85 °C |
| Protection class IP | IP67           |

## Standards, specifications, approvals

|                            |     |
|----------------------------|-----|
| Certificate of suitability |     |
| • UL approval              | Yes |

## Further Information / Internet Links

|                                                   |                                                                                                     |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Internet-Link                                     |                                                                                                     |
| • to website: Selector SIMATIC NET SELECTION TOOL | <a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>                               |
| • to website: Industrial communication            | <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>                 |
| • to website: Industry Mall                       | <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>                   |
| • to website: Information and Download Center     | <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> |
| • to website: Image database                      | <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>             |
| • to website: CAx Download Manager                | <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>                                 |
| • to website: Industry Online Support             | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>             |

**last modified:** 10/14/2016