

SURGE SUPPRESSOR RC ELEMENT AC 127 TO 240V/DC 150 TO 250V FOR PLUGGING ONTO CONTACTORS WITHOUT/WITH AUX.CONTACT BLOCKS



Figure similar

General technical data:

Product designation		surge suppressor
Design of the surge suppressor		with RC elements

Control circuit/ Control:

Type of voltage of the control supply voltage		AC/DC
Control supply voltage frequency		
• 1 rated value	Hz	50
• 2 rated value	Hz	60
Control supply voltage 1		
• at DC		
— Initial rated value	V	150
— Final rated value	V	250
• at AC		
— at 50 Hz Initial rated value	V	127
— at 50 Hz Final rated value	V	240
— at 60 Hz Final rated value	V	240

— at 60 Hz Initial rated value

V

127

Certificates/ approvals:

General Product Approval	Test Certificates	Shipping Approval
 CSA	 UR	
	spezielle Prüfbescheinigunge n	 DNV
		 PRS

Shipping Approval	other
 RINA	Bestätigungen sonstig Umweltbestätigung

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX4490-3T>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX4490-3T>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX4490-3T&lang=en

last modified:

10/07/2016