

SWITCH DISCONNECTOR NEW DESIGN IU=400A, UE=690V, 4-
POLE BASIC VERSION WITHOUT 8UC6 HANDLE AND SHAFT
4TH POLE SWITCHABLE, AC-21A



Figure similar

Model	
product brandname	SENTRON
Product designation	Switch Disconnecter 3KA
Design type	For mounting and installation
Insulation voltage / rated value	1 000 V
Protection class	
Protection class IP	IP00
Dissipation	
Power loss [W]	
for rated value of the current / at AC / in hot operating state / per pole	24 W
maximum	72 W
Electricity	
Let-through current / I _{2 t} / maximum permissible / in utilization category / AC-22 B / at 400 V	2 150 000 A ² ·s
Main circuit	

Number of poles / for main current circuit	4
Operating power	
• at AC-23 A / at 400 V / at 50/60 Hz / rated value	200 000 W
• at AC-23 A / at 500 V / at 50/60 Hz / rated value	200 000 W
• at AC-23 A / at 690 V / at 50/60 Hz / rated value	280 000 W
Operating voltage	
• at AC / at 50/60 Hz / rated value	690 V
• at DC / rated value	440 V
Rated current I_e / maximum / in utilization category	
• AC-21 A / at 400 V	400 A
• AC-21 A / at 500 V	400 A
• AC-21 B / at 400 V	400 A
• AC-21 B / at 500 V	400 A
• AC-22 A / at 400 V	400 A
• AC-22 A / at 500 V	400 A
• AC-22 B / at 400 V	400 A
• AC-22 B / at 500 V	400 A

Short circuit

Maximum short-circuit current breaking capacity (I _{cu}) / at 400 V / rated value	65 kA
Conditional rated short-circuit current	
• 400V	50 kA
• 500V	50 kA
• in utilization category / AC-21 A / at 400 V	50 kA
• in utilization category / AC-21 A / at 500 V	50 kA
• in utilization category / AC-21 B / at 400 V	50 kA
• in utilization category / AC-21 B / at 500 V	50 kA
• in utilization category / AC-22 A / at 400 V	50 kA
• in utilization category / AC-22 A / at 500 V	50 kA
• in utilization category / AC-22 B / at 400 V	50 kA
• in utilization category / AC-22 B / at 500 V	50 kA

Connections

Connectable conductor cross-section	
• for main contacts — stranded / maximum	240 mm ²
Type of connection, main circuit	Flat-type screw terminal
Type of electrical connection	
• for main current circuit	flat connector

Mechanical Design

Height	160 mm
Width	293 mm

Depth	207 mm
Type of mounting	fixed mounted
Mounting position	any
Mounting type	floor mounting
Mounting type	
• front mounting with 4-hole attachment	No
• front mounting with central attachment	No
• rail mounting	No

Environmental conditions

Ambient temperature

- | | |
|------------------------------|--------|
| • during operation / minimum | -25 °C |
| • during operation / maximum | 55 °C |
| • during storage / minimum | -50 °C |
| • during storage / maximum | 80 °C |

Certificates

Equipment marking

- acc. to DIN EN 61346-2

Q

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval	other
--------------------------	---------------------------	-------------------	-------------------	-------



CCC



EG-Konf.

[spezielle
Prüfbescheinigunge
n](#)



GL

[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3KA5740-1AE01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3KA5740-1AE01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KA5740-1AE01

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>