

SIMATIC DP, ELECT. SUBMODULE FOR ET 200ISP, 4 DO, DC
25.5V/22MA, "L"-SHUT DOWN



Figure similar

Input current	
from load voltage L+ (without load), max.	400 mA
Power loss	
Power loss, typ.	2.8 W
Address area	
Address space per module	
• without packing	2 byte
Digital outputs	
Number of digital outputs	4; additionally 1 intrinsically-safe input for L shutdown
Short-circuit protection	Yes
No-load voltage U _{ao} (DC)	25.5 V
Internal resistor R _i	260 Ω
Trend key points E	
• Voltage U _e (DC)	19.8 V
• Current I _e	22 mA
Output current	

• for signal "1" rated value	0.022 A
Output delay with resistive load	
• "0" to "1", max.	2 ms
• "1" to "0", max.	1.5 ms
Parallel switching of two outputs	
• for uprating	No
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz
Cable length	
• shielded, max.	500 m
• unshielded, max.	500 m
Interrupts/diagnostics/status information	
Status indicator	Yes
Diagnostic functions	Yes
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnostic messages	
• Diagnostic information readable	Yes
• Wire-break	Yes; $R > 10 \text{ kohms}$, $I < 100 \mu\text{A}$
• Short-circuit	Yes; $R < 80 \text{ ohms}$
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital output (green)	Yes; Per channel
Parameter	
Diagnostics wire break	Yes
Diagnostics short-circuit	Yes
Response to CPU/master STOP	Substitute a value/keep last value
Ex(i) characteristics	
Maximum values of output circuits (per channel)	
• Co (permissible external capacity), max.	81 nF; For IIC, 651 nF for IIB
• Io (short-circuit current), max.	110 mA
• Lo (permissible external inductivity), max.	1.7 mH; For IIC, 11.5 mH for IIB
• Po (power of load), max.	764 mW
• Uo (output no-load voltage), max.	27.9 V
Potential separation	
Potential separation digital outputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes

Permissible potential difference	
between different circuits	60 V DC/30 V AC
Standards, approvals, certificates	
CE mark	Yes
Highest safety class achievable in safety mode	
• SIL acc. to IEC 61508	No
Use in hazardous areas	
• Type of protection acc. to EN 50020 (CENELEC)	II 2 G (1) GD and I M2 Ex ib[ia][iaD] IIC T4; Ex ib [ia] I
• Type of protection acc. to KEMA	04 ATEX 1249
Dimensions	
Width	30 mm
Height	129 mm
Depth	136.5 mm
Weights	
Weight, approx.	255 g
last modified:	10/28/2016