

SITOP CNX8600 4X10A
SITOP CNX8600 4X 10A EXTENSION MODULE FOR PSU8600
OUTPUT: 24 V/4X 10 A DC



Output	
Output	Controlled, isolated DC voltage
Number of outputs	4
Rated voltage V_{out} DC	24 V
Output voltage	
• at output 1 at DC Rated value	24 V
• at output 2 at DC Rated value	24 V
• at output 3 at DC Rated value	24 V
• at output 4 at DC Rated value	24 V
Total tolerance, static $\pm$	3 %
Static mains compensation, approx.	0.2 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	100 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	200 mV
Adjustment range	5 ... 28 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer; Derating > 24 V: 4%/V; max. 240 W per output
Status display	3-color LED for operating state module; 3-color LED per output for operating state output

Signaling	Relay contact (changeover contact, contact current capacity DC 60 V/0.3 A) for "Operating state OK" at power supply unit PSU8600
On/off behavior	No overshoot of Vout (soft start)
Startup delay, max.	1.5 s; Without on-delay of the outputs
connection of outputs operating	Simultaneous connecting-in of all outputs after device booting or delay time of 25 ms, 100 ms or "load-optimized" for sequential cutting-in of the outputs via DIP switches at power supply unit PSU8600 can be set
Voltage increase time of the output voltage maximum	500 ms
Rated current value Iout rated	40 A
Output current • per output • at output 1 Rated value • at output 2 Rated value • at output 3 Rated value • at output 4 Rated value	10 A 10 A 10 A 10 A 10 A
Current range • Note	0 ... 40 A No increase in the maximum output power of the overall system SITOP PSU8600 via the expansion module SITOP CNX8600 possible
Supplied active power typical	960 W
Product feature parallel switching of outputs	No
Parallel switching for enhanced performance	No

Efficiency

Efficiency at Vout rated, Iout rated, approx.	97 %
Power loss at Vout rated, Iout rated, approx.	30 W

Closed-loop control

Dynamic mains compensation (Vin rated $\pm 15\%$), max.	0.1 %
Dynamic load smoothing (Iout: 50/100/50 %), Uout $\pm$ typ.	0.4 %
Setting time maximum	10 ms

Protection and monitoring

Output overvoltage protection	< 35 V
Property of the output Short-circuit proof	Yes
Short-circuit protection	electronic overload cut-off
adjustable response value current of current-dependent overload trip	0.5 ... 10 A
type of threshold value setting	via potentiometer
characteristics of electronic overload switch-off	Ia > 1.0 ... < 1.5 x Ia threshold permissible for 5 s; Ia limit (= 1.5 x Ia threshold) permissible for 200 ms
Reset	Via sensor per output

Remote reset	Non-electrically isolated 24 V input (signal level "high" at > 15 V) at power supply unit PSU8600
Overload/short-circuit indicator	3-color LED for operating state module; 3-color LED per output for operating state output

Interface

Specification interface	Ethernet/PROFINET via power supply unit PSU8600
-------------------------	---

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class III
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
Explosion protection	IECEx Ex nA IIC T4 Gc; ATEX (EX) II 3G Ex nA IIC T4 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4
FM approval	-
CB approval	Yes
Marine approval	GL; ABS in process
Degree of protection (EN 60529)	IP20

EMC

Emitted interference	EN 55022 Class B
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature	
during operation	-25 ... +60 °C
— Note	with natural convection
during transport	-40 ... +85 °C
during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics

Connection technology	Plug-in terminals with screwed connection
Connections	
Output	1, 2, 3, 4: Two plug-in terminals (1, 2 and 3, 4) with 2 screwed connections each for 0.2 ... 2.5 mm ² ; Ground: Plug-in terminal with 3 screwed connections for 0.2 ... 2.5 mm ²
Product function	
removable terminal at output	Yes
Suitability for interaction modular system	Yes
Type of connection to system components	Via integrated connector
Width of the enclosure	60 mm

Height of the enclosure	125 mm
Depth of the enclosure	150 mm
Required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
Weight, approx.	1.15 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x15
Mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
MTBF at 40 °C	499 861 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)