

Product type designation

CP 1243-1

COMMUNICATIONS PROCESSOR CP 1243-1 FOR CONNECTING SIMATIC S7-1200 TO TELECONTROL SERVER BASIC VIA ETHERNET ALSO SUITED FOR SAFE COMMUNICATION WITH NETWORK WITH FIREWALL AND VPN



Transmission rate

Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

1

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet
- for power supply

1

0

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet

RJ45 port

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Consumed current

- from backplane bus / at DC / at 5 V / typical

0.25 A

Power loss [W]

1.25 W

Permitted ambient conditions

Ambient temperature	
• for vertical installation / during operation • for horizontally arranged busbars / during operation • during storage • during transport	-20 ... +60 °C -20 ... +70 °C -40 ... +70 °C -40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-1200 single width
Width	30 mm
Height	110 mm
Depth	75 mm
Net weight	0.122 kg
Mounting type	
• 35 mm DIN rail mounting • wall mounting	Yes Yes

Product properties, functions, components / general

Number of units	
• per CPU / maximum	3

Performance data / S7 communication

Number of possible connections / for S7 communication	
• Note	like CPU

Performance data / telecontrol

Suitability for use	
• Node station • substation • TIM control center	No Yes No
Control center connection	to be used with Telecontrol Server Basic supported
• by means of a permanent connection • Note	Connection to SCADA system via Telecontrol Server Basic
Protocol / is supported	
• DNP3 • IEC 60870-5	No No
Product function / data buffering if connection is aborted	Yes; 64,000 values
Number of data points per station / maximum	200

Performance data / Teleservice

Diagnostics function / online diagnostics with SIMATIC STEP 7	Yes
Product function	
• program download with SIMATIC STEP 7	Yes
• Remote firmware update	Yes
Configuration software	
• required	STEP 7 Basic/Professional V13 Update 2 + HSP (TIA Portal) or higher

Product functions / Security

Firewall version	stateful inspection
Product function / with VPN connection	IPSec
Type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168
Type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
Type of hashing algorithms / with VPN connection	MD5, SHA-1
Number of possible connections / with VPN connection	8
Product function	
• password protection for Web applications	No
• password protection for teleservice access	No
• encrypted data transmission	Yes
• ACL - IP-based	No
• ACL - IP-based for PLC/routing	No
• switch-off of non-required services	Yes
• Blocking of communication via physical ports	No
• log file for unauthorized access	No

Product functions / Time

Protocol / is supported	
• NTP	Yes
time synchronization	
• from control center	Yes

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

10/21/2016