

Product type designation

Antenna RF642A

SIMATIC RF600 ANTENNA RF642A LINEAR (BROAD BAND)

FREQUENCY RANGE 865 TO 928 MHZ DIMENSIONS

185X185X45 MM (LXWXH); IP 65, -25 TO +55 DEGREES/C;



Suitability for operation	SIMATIC RF600
Wireless frequencies	
Transmission frequency	865 ... 928 MHz
Electrical data	
Impedance	50 Ω
Polarization	Linear
Antenna gain compared to spherical radiator	
• with linear radiation	6 dB
Standing wave ratio (VSWR) / maximum	1.5
Radiating angle of the antenna	
• horizontal	75°
• vertical	70°
Type of electrical connection / of the antenna	RP-TNC
Design of plug-in connection	male
Mechanical data	
Material	PA 12
Color	Pastel turquoise

Tightening torque / of the screw for securing the equipment / maximum	2 N·m
Mounting distance relating to metal surfaces / recommended / minimum	0 m

Permitted ambient conditions

Ambient temperature - during operation - during storage - during transport	-25 ... +75 °C -40 ... +85 °C -40 ... +85 °C
Protection class IP	IP65
Shock resistance	according to EN 60068-2-27
Shock acceleration	300 m/s ²
Vibrational acceleration	100 m/s ²

Design, dimensions and weight

Width	185 mm
Height	185 mm
Depth	45 mm
Net weight	600 g
Mounting type	4 screws M4 according to VESA 100, optional with articulated bracket by using antenna mounting kit
Wire length / of antenna cable	0 m

Product properties, functions, components / general

Product feature / silicon-free	Yes
--------------------------------	-----

Standards, specifications, approvals

Certificate of suitability	CE (according to R&TTE), FCC (Title 47, Part 15.247), cULus
----------------------------	---

Accessories

accessories	Antenna cables 1 to 40 m
-------------	--------------------------

Further Information / Internet Links

Internet-Link - to website: Selector SIMATIC NET SELECTION TOOL - to website: Industrial communication - to website: Industry Mall - to website: Information and Download Center - to website: Image database - to website: CAx Download Manager - to website: Industry Online Support	https://support.industry.siemens.com/cs/ww/en/view/67384997 http://www.siemens.com/ident/rfid https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
--	---

last modified: 09/14/2016