

SINAMICS BRAKING RESISTOR R=30Ohm P_{rated}=925W
P_{max}=18500W/12s/5% duty STANDALONE



Order number	
Phase number / of the input voltage	Wert fehlt!
Type of voltage / of the input voltage	Wert fehlt!
Input voltage	Wert fehlt! ... Wert fehlt!
Consumed active power / rated value	0.925 kW
• maximum	18.5 kW
Type of electrical connection / for power cable	Terminal block
Connectable conductor cross-section / for power cable	6 mm ²
Design of the temperature switch	Normally closed contact
Input voltage / of the temperature switch / at AC / maximum	Wert fehlt!
Input current / of the temperature switch / at AC / maximum	2.5 A
Connectable conductor cross-section / on the temperature switch / maximum	2.5 mm ²
Type of electrical connection / of the protective conductor connection	Yes
Design of the protective conductor connection / on enclosure	M4 screw
Protection class IP	IP20

Electrical resistance / of the braking resistor	30 Ω
Width	250 mm
Height	490 mm
Depth	140 mm
Net weight	6.2 kg

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SL3201-0BE23-8AA0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SL3201-0BE23-8AA0/all>