

Data sheet

6GT2690-0AK00

Product type designation

Product description

Distance piece MDS D124/D324/D424/RF320T

Support for mounting transponders with 27 mm diameter and 15 mm distance to metal

MOBY D / RF300 ISO / RF200 SPACER FOR MDS D124 / D324 / D424 / D524 and RF320T DIAMETER 35 MM; HEIGHT 15 MM; TEMPERATURE RANGE UP TO +180 C PACKAGING UNIT = MINIMAL ORDER QUANTITY 20 PIECES



Suitability for use

Support is mounted with an M4 countersunk head screw, the transponder is snapped on

Mechanical data

Material

PPS

Color

black

Permitted ambient conditions

Ambient temperature

- during operation -25 ... +125 °C
- during storage -40 ... +125 °C
- during transport -40 ... +125 °C

Design, dimensions and weight

Height

15 mm

Diameter

35 mm

Further Information / Internet Links

Internet-Link

- to website: TIA Selection Tool
- to website: Selector SIMATIC NET
SELECTION TOOL
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

last modified:

<http://www.siemens.com/tia-selection-tool>
<https://support.industry.siemens.com/WW/view/en/67384964>
<http://www.siemens.com/iwlan>
<http://www.siemens.com/ident/rfid>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

10/15/2016