


CIRCUIT-BREAKER VL 630N STANDARD BREAKING CAPACITY
ICU=55KA / 415 V AC 3 POLE, NON-AUTOMATIC OVERCURRENT
RELEASE MAGNETIC IN=630A, RATED CURRENT II=6300A,
SHORT CIRCUIT



Model	
Type of the driving mechanism / motor drive	No
Design of the overcurrent release	M
General technical data	
Number of poles	3
Size of the circuit-breaker	3VL5
Electrical endurance (switching cycles) / typical	5 000
Usage category	A
Performance class for circuit breaker	N
Mechanical service life (switching cycles) / typical	10 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	Q
Operating frequency / maximum	60 1/s
Voltage	
Rated operational voltage Ue / max.	690 V
Insulation voltage	
• rated value	800 V
• at AC / rated value	800 V

Surge voltage resistance / rated value	8 kV
Protection class	
Protection class IP	IP20
Protective function of the overcurrent release	I
Electricity	
Continuous current / rated value	630 A
Derating temperature / for the rated value of the continuous current	50 °C
Adjustable pick-up value current	
• of instantaneous short-circuit trip unit / initial value	6 300 A
• of instantaneous short-circuit trip unit / Full-scale value	6 300 A
Main circuit	
Operating frequency	
• 1 / rated value	50 Hz
• 2 / rated value	60 Hz
Operating voltage	
• for main current circuit / at AC / at 50 Hz / maximum	690 V
• for main current circuit / at AC / at 60 Hz / maximum	690 V
Operating current	
• at 40 °C / rated value	630 A
• at 50 °C / rated value	630 A
• at 55 °C / rated value	585.9 A
• at 60 °C / rated value	585.9 A
• at 65 °C / rated value	541.8 A
• at 70 °C / rated value	541.8 A
Suitability	
Suitability for use	non-automatic circuit-breakers
Product details	
Product component	
• Trip indicator	No
• Auxiliary switch	No
• Voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
Product extension / optional / motor drive	Yes
Product function	
Product function	

- of thermal overload trip unit
- Ground fault protection
- for neutral conductors / Short-circuit and overload proof
- Overload protection

without
No
No
No

Short circuit

Operational short-circuit current breaking capacity (Ics)

- at 240 V / rated value 65 kA
- at 415 V / rated value 55 kA
- at 500 V / rated value 20 kA
- at 690 V / rated value 10 kA

Maximum short-circuit current breaking capacity (Icu)

- at 240 V / rated value 65 kA
- at 415 V / rated value 55 kA
- at 440 V / rated value 35 kA
- at 480 V / acc. to NEMA / rated value 25 kA
- at 500 V / rated value 25 kA
- at 600 V / acc. to NEMA / rated value 20 kA
- at 690 V / rated value 20 kA

Connections

- Arrangement of electrical connectors / for main current circuit front side
- Type of electrical connection / for main current circuit screw-type terminals

Mechanical Design

- Height 279.5 mm
- Width 190 mm
- Depth 138.5 mm
- Mounting type fixed mounting

Environmental conditions

Ambient temperature

- during operation / minimum 0 °C
- during operation / maximum 70 °C
- during storage / minimum -40 °C
- during storage / maximum 80 °C

Certificates

- Certificate of suitability IEC, standard switching capacity (N)
- Equipment marking
 - acc. to DIN EN 61346-2 Q

General Product Approval	EMC	Declaration of Conformity
--------------------------	-----	---------------------------



[sonstig](#)



[TSE](#)



Test Certificates	Shipping Approval
-------------------	-------------------

[spezielle
Prüfbescheinigunge
n](#)



other

[Umweltbestätigung](#)

[Bestätigungen](#)

[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL5763-1DE36-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL5763-1DE36-0AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL5763-1DE36-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>