

TOUCH PEN, THIN FOR RESISTIVE TOUCHSCREEN HOLDING CORD FOR MOBILE PANEL 277 10" AND OTHER RESISTIVE TOUCH DISPLAYS AMOUNT AND CONTENT: SEE TECHNICAL DATA



General information	
Product type designation	Touch pen, thin, resistive technology
Control elements	
Frame size/design	
• Standard	Yes; For industrial applications
Installation type/mounting	
Wall mounting/direct mounting possible	Yes; using 40 cm retaining cord
Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C
• max.	80 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	80 °C
Relative humidity	
• Operation, max.	90 %
Mechanics/material	

Material	
• Plastic	Yes
Screw type	
• Torx	No
Dimensions	
Height	125 mm; Length
Thickness	8 mm; Diameter
Scope of supply	
Delivery quantity in pieces	5; Incl. retaining cord for Mobile Panel 277 10"
Other	
Target devices	for resistive touch screens
Usable in the following products	
• Product 1	6av2124-0*
• Product 2	6AV2123-2*
• Product 3	6AV6642-0BD01-3AX0
• Product 4	6AV6642-0BA01-1AX1
• Product 5	6AV6642-0BC01-1AX1
• Product 6	6AV6642-0DC01-1AX0
• Product 7	6AV6642-0DA01-1AX0
• Product 8	6AV6545-0DA10-0AX0
• Product 9	6AV6545-0DB10-0AX0
• Product 10	6AV6545-0AA15-2AX0
• Product 11	6AV3637-1PL00-0AX0
• Product 12	6AV6642-0EA01-3AX0
• Product 13	6AV6644-0CB01-2AX0
• Product 14	6AV6643-8AD10-0AA0
• Product 15	6AV6640-0CA01-0AX0
• Product 16	6AV6545-0AH10-0AX*
• Product 17	6AV6642-0AA11-0AX*
• Product 18	6AV6640-0CA01-0AX0
• Product 19	6AV6545-0CC10-0AX0
• Product 20	6AV2123-2*
• Product 21	6AV2124-0QC13-0AX0
• Product 22	6AV2124-0GC13-0AX0
last modified:	10/28/2016