

Data sheet

6XV1820-6AH10

Product type designation

Product description

Flexible fiber optic trailing cable

Flexible glass fiber-optic cable, sold by the meter, unassembled
SIMATIC NET, FLEXIBLE FIBER OPTIC CABLE (62.5/125),
TRAILING CABLE, SPLITTABLE, WITHOUT CONNECTOR, SOLD
BY THE METER MAX. CONSIGNMENT: 2000 M MIN. ORDER
QUANTITY: 20 M



Suitability for use	Flexible cable for installation in cable carriers indoors and outdoors
Version of the assembled FO cable	For assembly with four BFOC connectors
Cable designation	AT-W11Y(ZN)11Y 2 G 62.5/125

Optical data

Damping ratio per length	
• at 850 nm / maximum	3.1 dB/km
• at 1300 nm / maximum	0.8 dB/km
Bandwidth length product	
• at 850 nm	200 GHz·m
• at 1300 nm	600 GHz·m

Mechanical data

Number of fibers / per FOC core	1
Number of FO cores / per FOC cable	2
Version of the FO conductor fiber	Multimode graded-index fiber 62.5/125 µm, OM 1
Design of the FOC core	Hollow core, filled, diameter 1400 µm
Design of the fiber-optic cable	Segmentable outer conductor

Outer diameter	
• of the optical fibers	62.5 µm
• of the optical fiber sheath	125 µm
• of the FOC core sheath	3.5 mm
Outer diameter / of the cable	12.9 mm
Material	
• of the fiber-optic cable core	Quartz glass
• of the optical fiber sheath	Quartz glass
• of the FOC core sheath	PUR
• of the fiber-optic cable sheath	PUR
• of the strain relief	Aramid fibers, also GRP central element
Color	
• of the FOC core sheath	black
• of cable sheath	Black
Bending radius	
• with single bend / minimum permissible	150 mm
• with multiple bends / minimum permissible	150 mm
Number of bending cycles	100000
Tensile load	
• during installation / short-term	2000 N
• during operation / maximum	1000 N
Weight per length	130 kg/km

Permitted ambient conditions

Ambient temperature	
• during operation	-30 ... +60 °C
• during storage	-30 ... +70 °C
• during transport	-30 ... +70 °C
• during installation	-30 ... +60 °C
Burning behavior	flammable
Chemical resistance	
• to mineral oil	acc. to IEC 60811-404 with test oil IRM 902 (acc. to ISO 1817), +100 °C, 168 h, pull speed 250 mm/min
• to grease	resistant
• to water	conditional resistance
Radiological resistance / to UV radiation	resistant

Product properties, functions, components / general

Product feature	
• halogen-free	Yes
• silicon-free	Yes
Product component / Rodent protection	No
Wire length	

- | | |
|--|--------|
| • for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum | 4000 m |
| • for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum | 350 m |
| • for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum | 550 m |
| • for glass FOC / with PROFIBUS / maximum | 3000 m |

Standards, specifications, approvals

Certificate of suitability

- | | |
|-------------------|-----|
| • RoHS conformity | Yes |
|-------------------|-----|

Further Information / Internet Links

Internet-Link

- | | |
|---|---|
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAx Download Manager | http://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |

last modified: 10/12/2016