

SIPLUS LOGO! DM8 24 -40 ... +70 DEGREES C BASED ON
6ED1055-1CB00-0BA0



Installation type/mounting	
Mounting	on 35 mm DIN rail, 2 spacing units wide
Supply voltage	
Rated value (DC)	Yes
• 24 V DC	
permissible range, lower limit (DC)	20.4 V; 22 V @ >55 °C
permissible range, upper limit (DC)	28.8 V; 27.5 V @ >55 °C
Digital inputs	
Number of digital inputs	4
Input voltage	
• Type of input voltage	DC
Digital outputs	
Number of digital outputs	4; Transistor
Short-circuit protection	Yes
Output current	
• for signal "1" rated value	0.3 A; 0.2 A @ > 55 °C; 0.3 A @ > 55 °C & < 15 s
EMC	

Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes
Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP20	Yes
Standards, approvals, certificates	
CSA approval	No
UL approval	Yes; File: E120869 // Tmax = 55 °C
FM approval	No
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	
• Marine approval	No
Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C; = Tmin
• max.	70 °C; = Tmax; 55 °C @ UL/cUL use
Extended ambient conditions	
• relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity	
— With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; Relative humidity, incl. condensation / frost permitted (no commissioning under condensation conditions)
Resistance	
— against biologically active substances / conformity with EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!
— against chemically active substances / conformity with EN 60721-3-3	Yes; Class 3C4 incl. salt spray. The supplied connector covers must remain on the unused interfaces during operation!
— against mechanically active substances / conformity with EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!
Dimensions	
Width	36 mm; 2 DU
Height	90 mm
Depth	55 mm
last modified:	10/28/2016