

Data sheet

6GK1901-1BE00-0AA0

Product type designation

IE FC RJ45 modular outlet (without insert)
 INDUSTRIAL ETHERNET FASTCONNECT RJ45 MODULAR
 OUTLET BASE MODULE, CAT6, WITHOUT INSERT, PACK = 1 PC



Electrical data

Transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
---------------	------------------------------------

Interfaces

Number of electrical connections	1
for Industrial Ethernet FC TP cables	
Type of electrical connection	integrated insulation displacement contacts
for Industrial Ethernet FC TP cables	
FastConnect	

Mechanical data

Material / of the enclosure	metal
-----------------------------	-------

Design, dimensions and weight

Width	50 mm
Height	115.25 mm
Depth	58.95 mm
Net weight	450 g
Mounting type	Yes
35 mm DIN rail mounting	

- wall mounting

Yes

Permitted ambient conditions

Ambient temperature	
• during operation	-20 ... +70 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP40

Standards, specifications, approvals

Certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
Standard for structured cabling	Cat 6

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified:

10/19/2016