

Product type designation



SCALANCE W786-1 RJ45

IWLAN Access Point, SCALANCE W786-1 RJ45, 1 radio, 3 R-SMA antenna connector, iFeatures support via KEY-PLUG, IEEE 802.11a/b/g/h/n, 2,4/5GHz, brutto 450 MBit/s per radio, 1x RJ45 max. 1 Gbit/s, PoE, redundant DC 24 V, term. block, 110 - 230 V AC via PS791-2AC IP65, -40...+60°C, plug slot, WPA2/802.11i/e, Note national approvals! CERT ID: EAPN-W1-RJ-E3, contains: MPCIE-R1-ABGN-U3, scope of supply: manuals on CD, German/English, 1x terminal block; for use outside USA/Israel

Transmission rate

Transfer rate

- | | |
|---------------------------|--|
| • with WLAN / maximum | 450 Mbit/s |
| • for Industrial Ethernet | 10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10 Mbit/s, 1000 Mbit/s |

Interfaces

Number of electrical connections

- | | |
|--|---|
| • for network components or terminal equipment | 1 |
| • for power supply | 1 |
| • for redundant voltage supply | 1 |

Type of electrical connection

- | | |
|--|--|
| • for network components or terminal equipment | RJ45 socket |
| • for power supply | 2-pole connector (24 V DC) or optionally available power supply adapter (4-pole 24 V DC or 3-pole 110 to 230 V AC) |

design of the removable storage

- | | |
|------------|-----|
| • C-PLUG | Yes |
| • KEY-PLUG | Yes |

Interfaces / wireless

Number of radio cards / permanently installed	1
Transmission mode / for multiple input multiple output (MIMO)	3x3
Number of spatial streams	3
Number of electrical connections / for external antenna(s)	3
Type of electrical connection / for external antenna(s)	R-SMA (socket)
Product feature / external antenna can be mounted directly on device	No

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / 1 • from terminal block	19.2 V
Supply voltage / 2 • from terminal block	28.8 V
Supply voltage • from Power-over-Ethernet acc. to IEEE802.3at for type 1 and IEEE802.3af • from Power-over-Ethernet acc. to IEEE802.3at for type 2 • from optional integrable power supply — at AC — at DC	48 V 50 V 100 ... 240 V 12 ... 24 V
Consumed current • at DC / at 24 V / typical • at AC / at 230 V / typical • with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	0.45 A 0.05 A 0.22 A
Power loss [W] • at DC / at 24 V / typical • at AC / at 230 V / typical • with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	10.7 W 10.7 W 10.7 W

Permitted ambient conditions

Ambient temperature • during operation • during storage • during transport	-40 ... +60 °C -40 ... +85 °C -40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	100 %
Ambient condition / for operation	When using the power supply 100 to 240 V AC, an operating temperature of -40 °C to +60 °C is permissible
Protection class IP	IP65

Design, dimensions and weight	
Width / of the enclosure / without antenna	251 mm
Height / of the enclosure / without antenna	251 mm
Depth / of the enclosure / without antenna	72 mm
Net weight	2.24 kg
Mounting type	For mast mounting, 35 mm DIN rail mounting and S7-300 rail mounting, an additional support plate is required
• S7-300 rail mounting	Yes
• S7-1500 rail mounting	No
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

Wireless frequencies	
Operating frequency	
• for WLAN in 2.4 GHz frequency band	2.41 ... 2.48 GHz
• for WLAN in 5 GHz frequency band	4.9 ... 5.8 GHz

Product properties, functions, components / general	
Product function / Access Point Mode	Yes
Product function / Client Mode	Yes
Number of SSIDs	8
Product function	
• iPCF Access Point	Yes; Only in combination with the 'KEY-PLUG W780 iFeatures'
• iPCF client	Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures'
• iPCF-MC Access Point	No
• iPCF-MC client	Yes; Only in combination with 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures'
Number of iPCF-capable radio modules	1
Product function / iREF	Yes; In combination only with 'KEY-PLUG W780 iFeatures'
Number of iREF-capable radio modules	1

Product functions / management, configuration	
Number of manageable IP addresses / in client	8
Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• configuration with STEP 7 in the TIA Portal	Yes
• operation with IWLAN controller	No
• operation with Enterasys WLAN controller	No
• WDS	Yes

Protocol / is supported	
• Address Resolution Protocol (ARP)	Yes
• ICMP	Yes
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• DCP	Yes
• LLDP	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher-level designation/location designation	Yes

Product functions / Diagnosis

Product function	
• PROFINET IO diagnosis	Yes
• Link Check	No
• connection monitoring IP-Alive	No
• localization via Aeroscout	Yes
• SysLog	Yes
Protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes

Product functions / VLAN

Product function	
• function VLAN with IWLAN	Yes

Product functions / DHCP

Product function	
• DHCP client	Yes
• in Client Mode / DHCP server via LAN	Yes
• DHCP Option 82	Yes

Product functions / Redundancy

Protocol / is supported	
• STP/RSTP	Yes

Product functions / Security

Product function	
• ACL - MAC-based	Yes
• Management security, ACL-IP based	Yes
• IEEE 802.1x (radius)	Yes

• NAT/NAPT • access protection according to IEEE802.11i • WPA/WPA2 • TKIP/AES	No Yes Yes Yes
Protocol / is supported • SSH • RADIUS	Yes Yes
Product functions / Time	
Protocol / is supported • NTP • SNTP • SIMATIC Time	Yes Yes Yes
Standards, specifications, approvals	
Standard • for FM • for hazardous zone • for safety / from CSA and UL • for hazardous zone / from CSA and UL	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4 EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X UL 60950-1 CSA C22.2 No. 60950-1 ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC
Certificate of suitability • EC declaration of conformity • CE marking • C-Tick • CCC • E1 approval • Railway application in accordance with EN 50155 • NEMA TS2 • IEC 61375 • IEC 61850-3 • NEMA4X • Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af • Power-over-Ethernet according to IEEE802.3at for type 2	Yes Yes Yes No Yes No No No Yes Yes Yes
Standard for wireless communication • IEEE 802.11a • IEEE 802.11b • IEEE 802.11e • IEEE 802.11g	Yes Yes Yes Yes

• IEEE 802.11h • IEEE 802.11i • IEEE 802.11n	Yes
Wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
Marine classification association • American Bureau of Shipping Europe Ltd. (ABS) • Bureau Veritas (BV) • DNV GL • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) • Royal Institution of Naval Architects (RINA)	Yes Yes Yes Yes Yes Yes Yes

Accessories	
accessories	24 V DC screw terminal included in scope of delivery

Further Information / Internet Links	
Internet-Link	
• to website: TIA Selection Tool • to the website: IWLAN • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support	http://www.siemens.com/tia-selection-tool http://www.siemens.com/iwlan https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

Security information	
Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified: 10/19/2016