

22MM METAL ROUND COMPLETE UNIT COMBINATION:  
INDICATOR LIGHT WITH CONCENTRIC RINGS NON-  
ILLUMINATED WITH LAMP HOLDER BA 9S WITHOUT LAMP  
SCREW TERMINAL WITH HOLDER YELLOW



Figure similar

|                                                                                  |                     |
|----------------------------------------------------------------------------------|---------------------|
| Design of the product                                                            | Complete unit round |
| Enclosure:                                                                       |                     |
| Shape of the enclosure front                                                     | round               |
| Material of the enclosure                                                        | metal               |
| Number of command points                                                         | 0                   |
| Actuator:                                                                        |                     |
| Design of the operating mechanism                                                | indicator light     |
| Product extension optional Light source                                          | Yes                 |
| Color <ul style="list-style-type: none"><li>• of the actuating element</li></ul> | Yellow              |
| Shape of the actuating element                                                   | Concentric rings    |
| Type of unlocking device                                                         | without             |
| Number of switching positions                                                    | 0                   |
| Front ring:                                                                      |                     |
| Product component front ring                                                     | No                  |
| Holder:                                                                          |                     |

|                                                                     |                      |
|---------------------------------------------------------------------|----------------------|
| <b>Material of the holder</b>                                       | Metal                |
| <b>Contact block/ lampholder:</b>                                   |                      |
| <b>Mounting type</b>                                                | BA 9s without lamp   |
| <b>Number of lampholders</b>                                        | 1                    |
| <b>Number of switching elements</b>                                 | 0                    |
| <b>General technical data:</b>                                      |                      |
| <b>Product function</b>                                             |                      |
| • positive opening                                                  | No                   |
| <b>Product component</b>                                            |                      |
| • Light source                                                      | No                   |
| <b>Protection class IP</b>                                          | IP67                 |
| <b>Vibration resistance</b>                                         |                      |
| • acc. to IEC 60068-2-6                                             | 20 ... 200 Hz: 5g    |
| <b>Equipment marking</b>                                            |                      |
| • acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 | H                    |
| • acc. to DIN EN 61346-2                                            | P                    |
| • acc. to DIN EN 81346-2                                            | P                    |
| <b>Auxiliary circuit:</b>                                           |                      |
| <b>Number of NC contacts</b>                                        |                      |
| • for auxiliary contacts                                            | 0                    |
| <b>Number of NO contacts</b>                                        |                      |
| • for auxiliary contacts                                            | 0                    |
| <b>Number of CO contacts</b>                                        |                      |
| • for auxiliary contacts                                            | 0                    |
| <b>Connections/ Terminals:</b>                                      |                      |
| <b>Type of electrical connection</b>                                | screw-type terminals |
| <b>Tightening torque of the screws in the bracket</b>               | 1.4 ... 1.6 N·m      |
| <b>Ambient conditions:</b>                                          |                      |
| <b>Ambient temperature</b>                                          |                      |
| • during operation                                                  | -25 ... +60 °C       |
| • during storage                                                    | -40 ... +80 °C       |
| <b>Environmental category during operation acc. to IEC 60721</b>    | 3K6                  |
| <b>Installation/ mounting/ dimensions:</b>                          |                      |
| <b>Mounting type</b>                                                | front mounting       |
| <b>Shape of the installation opening</b>                            | round                |
| <b>Mounting diameter</b>                                            | 22 mm                |
| <b>Mounting height</b>                                              | 11 mm                |
| <b>Installation width</b>                                           | 28 mm                |

|                    |       |
|--------------------|-------|
| Installation depth | 49 mm |
|--------------------|-------|

#### Accessories:

|                                                   |    |
|---------------------------------------------------|----|
| Product component holder for 3 switching elements | No |
|---------------------------------------------------|----|

#### Certificates/approvals

| General Product Approval                                                                 | Declaration of Conformity                                                                     | Test Certificates                                  | Shipping Approval                                                                          |
|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|----------------------------------------------------|--------------------------------------------------------------------------------------------|
| <br>CCC | <br>EG-Konf. | <a href="#">spezielle Prüfbescheinigungen</a><br>n | <br>ABS |

| Shipping Approval                                                                         | other                             |
|-------------------------------------------------------------------------------------------|-----------------------------------|
| <br>DNV  | <a href="#">Bestätigungen</a>     |
| <br>LRS  | <a href="#">Umweltbestätigung</a> |
| <br>PRS  |                                   |
| <br>RINA |                                   |

| other                   |
|-------------------------|
| <a href="#">sonstig</a> |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3604-6BA30>

##### Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3604-6BA30>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3604-6BA30>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB3604-6BA30&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3604-6BA30&lang=en)



last modified:

10/07/2016