

Product type designation

TIM 4R-IE DNP3
TIM 4R-IE DNP3 COMMUNICATIONS MODULE FOR SIMATIC S7-300, S7-400, PC; WITH TWO RS232/RS485- INTERFACE FOR DNP3- COMMUNICATION VIA CLASSIC WAN NETWORKS AND TWO RJ45-INTERFACES FOR DNP3-COMMUNICATION VIA IP-BASED NETWORK (WAN OR LAN)



Transmission rate	
Transfer rate	
• for Industrial Ethernet	10 ... 100 Mbit/s
• acc. to RS 232	9600 ... 115200 bit/s
Interfaces	
Number of interfaces / acc. to Industrial Ethernet	2
Number of electrical connections	
• for external data transmission / acc. to RS 232	2
• for power supply	1
Type of electrical connection	
• of Industrial Ethernet interface	RJ45 port
• at interface 1 / for external data transmission	9 pin Sub-D-connector, RS232 switchable to RS485
• at interface 2 / for external data transmission	9-pole D-sub connector, RS232 can be switched to RS485
• for power supply	2-pole plugable terminal block
design of the removable storage / C-PLUG	Yes
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC

Supply voltage	24 V
Supply voltage	20.4 ... 28.8 V
Supply voltage / external / at DC / Rated value	24 V
Supply voltage / external / at DC / rated value	20.4 ... 28.8 V
Consumed current	
• from backplane bus / at DC / at 24 V / maximum	0.2 A
• from external supply voltage / at DC / at 24 V / maximum	0.17 A
Power loss [W]	4.6 W
Product extension / optional / Backup battery	Yes
Type of battery	Lithium AA / 3.6 V / 2.3 Ah
Backup current	
• typical	100 µA
• maximum	160 µA

Permitted ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-300 double width
Width	80 mm
Height	125 mm
Depth	120 mm
Net weight	0.4 kg

Product properties, functions, components / general

Number of units	
• Note	Number of TIMs per S7-300 / S7-400: 1
Wire length	
• with RS 232 interface / maximum	6 m
• with RS 485 interface / maximum	30 m

Performance data / S7 communication

Number of possible connections / for S7 communication	
• maximum	5
• with PG connections / maximum	2
• with OP connections / maximum	1

• Note	only via LAN
Service	
• PG/OP communication	Yes

Performance data / telecontrol

Suitability for use	
• Node station	Yes
• substation	Yes
• TIM control center	Yes
Protocol / is supported	
• TCP/IP	Yes
• DNP3	Yes
• SINAUT ST1 protocol	No
• SINAUT ST7 protocol	No
• Modbus RTU	Yes
Product function / data buffering if connection is aborted	Yes; 200,000 data points with one master
Number of DNP3 masters	
• for Ethernet / maximum	8
• with RS 232 interface / maximum	1
Number of Modbus RTU slaves / maximum	1
Configuration software	
• required	SINAUT ST7 ES
Storage location / of TIM configuration data	on the CPU or TIM

Product functions / Time

Product component / Hardware real-time clock	Yes
Product feature / Hardware real-time clock w. battery backup	Yes
Accuracy / of the hardware real-time clock / per day / maximum	4 s
time synchronization	
• from NTP-server	Yes

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAX Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

10/21/2016