

SIMATIC S7-400, SM 431 ANALOG INPUT MODULE OPTIC.
ISOLATED, 16 AI, 16 BIT RESOLUTION, U/I/RESIST./
THERMOEL./PT100,ALARM,DIAGNOST.



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V; Only required for supplying 2-wire transmitters
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	400 mA; for 16 connected, fully controlled 2-wire transmitters
from backplane bus 5 V DC, max.	700 mA
Power loss	
Power loss, typ.	4.5 W
Analog inputs	
Number of analog inputs	16
• For voltage/current measurement	16
• For resistance measurement	8
permissible input voltage for voltage input (destruction limit), max.	18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20)

permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	Yes
• Resistance thermometer	Yes
• Resistance	Yes
Input ranges (rated values), voltages	
• 1 V to 5 V	Yes
• Input resistance (1 V to 5 V)	1 M Ω
• -1 V to +1 V	Yes
• Input resistance (-1 V to +1 V)	1 M Ω
• -10 V to +10 V	Yes
• Input resistance (-10 V to +10 V)	1 M Ω
• -2.5 V to +2.5 V	Yes
• Input resistance (-2.5 V to +2.5 V)	1 M Ω
• -25 mV to +25 mV	Yes
• Input resistance (-25 mV to +25 mV)	1 M Ω
• -250 mV to +250 mV	Yes
• Input resistance (-250 mV to +250 mV)	1 M Ω
• -5 V to +5 V	Yes
• Input resistance (-5 V to +5 V)	1 M Ω
• -50 mV to +50 mV	Yes
• Input resistance (-50 mV to +50 mV)	1 M Ω
• -500 mV to +500 mV	Yes
• Input resistance (-500 mV to +500 mV)	1 M Ω
• -80 mV to +80 mV	Yes
• Input resistance (-80 mV to +80 mV)	1 M Ω
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	50 Ω
• -10 mA to +10 mA	Yes
• Input resistance (-10 mA to +10 mA)	50 Ω
• -20 mA to +20 mA	Yes
• Input resistance (-20 mA to +20 mA)	50 Ω
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	50 Ω
• -5 mA to +5 mA	Yes
• Input resistance (-5 mA to +5 mA)	50 Ω
Input ranges (rated values), thermocouples	

• Type B	Yes
• Type E	Yes
• Type J	Yes
• Type K	Yes
• Type L	Yes
• Type N	Yes
• Type R	Yes
• Type S	Yes
• Type T	Yes
• Type U	Yes
Input ranges (rated values), resistance thermometer	
• Ni 100	Yes
• Input resistance (Ni 100)	1 MΩ
• Ni 1000	Yes
• Input resistance (Ni 1000)	1 MΩ
• Pt 100	Yes
• Input resistance (Pt 100)	1 MΩ
• Pt 1000	Yes
• Input resistance (Pt 1000)	1 MΩ
• Pt 200	Yes
• Input resistance (Pt 200)	1 MΩ
• Pt 500	Yes
• Input resistance (Pt 500)	1 MΩ
Input ranges (rated values), resistors	
• 0 to 48 ohms	Yes
• Input resistance (0 to 48 ohms)	1 MΩ
• 0 to 150 ohms	Yes
• Input resistance (0 to 150 ohms)	1 MΩ
• 0 to 300 ohms	Yes
• Input resistance (0 to 300 ohms)	1 MΩ
• 0 to 600 ohms	Yes
• Input resistance (0 to 600 ohms)	1 MΩ
• 0 to 6000 ohms	Yes; Usable up to 5000 Ohm
• Input resistance (0 to 6000 ohms)	1 MΩ
Thermocouple (TC)	
Temperature compensation	
— external temperature compensation with compensations socket	Yes
— external temperature compensation with Pt100	Yes
— dynamic reference temperature value	Yes
Characteristic linearization	

• parameterizable — for thermocouples — for resistance thermometer	Yes Type B, E, J, K, L, N, R, S, T, U Pt100, Pt200, Pt500, Pt1000, Ni100, Ni1000
Cable length	
• shielded, max.	200 m; 50 m with thermocouples and input ranges ≤ 80 mV

Analog value generation for the inputs

Integration and conversion time/resolution per channel

• Resolution with overrange (bit including sign), max.	16 bit; 16 / 16 / 16
• Integration time, parameterizable	Yes
• Basic conversion time (ms)	6 / 20,1 / 23,5 ms
• Integration time (ms)	2,5 / 16,7 / 20 ms
• Basic conversion time, including integration time (ms) — additional conversion time for wire-break monitoring — additional conversion time for resistance measurement — additional conversion time for wire-break monitoring and resistance measurement	4.3 / 4.3 / 4.3 ms 12 / 40,2 / 47 ms 5,5 ms
• Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 Hz

Encoder

Connection of signal encoders

• for voltage measurement	Yes; possible
• for current measurement as 2-wire transducer	Yes
• for current measurement as 4-wire transducer	Yes
• for resistance measurement with two-wire connection	Yes; Line resistances are also measured
• for resistance measurement with three-wire connection	Yes
• for resistance measurement with four-wire connection	Yes

Errors/accuracies

Operational error limit in overall temperature range

• Voltage, relative to input range, (+/-)	0.3 %; +/-0.3% at +/-250 mV, +/-500 mV, +/-1 V, +/-2.5 V, +/-5 V, 1 to 5 V, +/- 10 V; +/-0.31% at +/-80 mV; +/-0.32% at +/-50 mV; +/-0.35% at +/-25 mV;
• Current, relative to input range, (+/-)	0.3 %; at 0 to 20 mA, +/-5 mA, +/-10 mA, +/- 20 mA, 4 to 20 mA

Resistance, relative to input range, (+/-)	0.3 %; +/-0.3% at 0 to 48 Ohm (4-conductor measurement), 0 to 150 Ohm (4-conductor measurement), 0 to 300 Ohm (4-conductor measurement), 0 to 600 Ohm (4-conductor measurement), 0 to 5000 Ohm (4-conductor measurement, in range of 6000 Ohm); +/- 0.4% at 0 to 300 Ohm (3-conductor measurement), 0 to 600 Ohm (3-conductor measurement), 0 to 5000 Ohm (3-conductor measurement, in range of 6000 Ohm);
Resistance thermometer, relative to input range, (+/-)	0.4 %
Basic error limit (operational limit at 25 °C)	
Voltage, relative to input range, (+/-)	0.15 %; $\pm 0.15\%$ at ± 250 mV, ± 500 mV, ± 1 V, ± 2.5 V, ± 5 V, 1 V to 5 V, ± 10 V; $\pm 0.17\%$ at ± 80 mV; $\pm 0.19\%$ at ± 50 mV; $\pm 0.23\%$ at ± 25 mV
Current, relative to input range, (+/-)	0.15 %; at 0 to 20 mA, +/-5 mA, +/-10 mA, +/- 20 mA, 4 to 20 mA
Resistance, relative to input range, (+/-)	0.15 %; +/-0.15% at 0 to 48 ohms (4-conductor measurement), 0 to 150 ohms (4-conductor measurement), 0 to 300 ohms (4-conductor measurement), 0 to 5000 ohms (4-conductor measurement, in range of 6000 ohms); +/-0.3% at 0 to 300 ohms (3-conductor measurement), 0 to 600 ohms (3-conductor measurement), 0 to 5000 ohms (3-conductor measurement, in range of 6000 ohms)
Resistance thermometer, relative to input range, (+/-)	0.3 %

Interrupts/diagnostics/status information

Diagnostics	Yes; Parameterizable
Alarms	
Diagnostic alarm	Yes; Parameterizable
Limit value alarm	Yes; Parameterizable

Potential separation

Potential separation analog inputs	
Potential separation analog inputs	Yes; internal/external
between the channels	No

Isolation

Isolation tested with	2120 V DC between bus and L+/M; 2120 V DC between bus and analog part; 500 V DC between bus and local ground; 707 V DC between analog part and L+/M; 2120 V DC between analog part and local ground; 2120 V DC between L+/M and local ground
-----------------------	--

Dimensions

Width	25 mm
Height	290 mm
Depth	210 mm

Weights

Weight, approx.	500 g
-----------------	-------

last modified:

10/28/2016