

WINDOW-TYPE CURRENT TRANSFORMER, CLASS 1 200A/1A,  
5VA PRIMARY CURRENT 200A, 5VA



Figure similar

| Model                                                           |                                  |
|-----------------------------------------------------------------|----------------------------------|
| Product designation                                             | Window-type current transformers |
| Protection class                                                |                                  |
| Protection class IP                                             | IP20                             |
| Connections                                                     |                                  |
| Type of electrical connection / at output                       | screw-type terminals             |
| Mechanical Design                                               |                                  |
| Height                                                          | 85.5 mm                          |
| Width                                                           | 64 mm                            |
| Width                                                           |                                  |
| • of the push-through bus bar / at 1 bus bar / maximum          | 30 mm                            |
| • of the push-through bus bar / in case of 2 bus bars / maximum | 25 mm                            |
| Depth                                                           | 80 mm                            |
| Mounting type                                                   | screw fixing                     |

|                                                          |       |
|----------------------------------------------------------|-------|
| Outer diameter / of the push-through conductor / maximum | 28 mm |
|----------------------------------------------------------|-------|

#### Environmental conditions

##### Ambient temperature

- during operation / minimum -10 °C
- during operation / maximum 55 °C

#### Certificates

Equipment marking / acc. to DIN EN 61346-2 T

##### General Product Approval

##### Declaration of Conformity



#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/4NC5222-0CE20>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/4NC5222-0CE20/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=4NC5222-0CE20](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4NC5222-0CE20)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>