

SINAMICS LINE REACTOR 380-480V 3AC 47-63HZ I_{LN} = 4,0A
STANDALONE



Order number	
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	380 ... 480
Output current / rated value	4 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	screw-type terminal
• for load-side outgoing feeder	screw terminals
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
• for load-side outgoing feeder	4 mm ²
Type of electrical connection / for PE conductor	M4 x 8, washer, spring lock washer
Protection class IP	IP20
Width	125 mm
Height	120 mm

Depth	71 mm
Net weight	1.1 kg
Certificate of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SL3203-0CE13-2AA0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SL3203-0CE13-2AA0/all>