

SCHUKO SOCKET 16A WITH EARTHING PIN ACC. TO CEE 7
FOR INSTALL. IN DISTRIB. BOARDS



Model	
Design of the product	others
Cover version	central plate
Design of the special power supply unit	without special current supply
Design of the socket / according to VDE 0620 for severe conditions	No
Design of the phase tap	No
General technical data	
Marking / of socket outlet	others
Surface processing	others
Material	thermoplastic
Protection class	
Protection class IP	IP20
Main circuit	
Operating frequency	
• minimum	50 Hz
• maximum	50 Hz
Operating voltage / Rated value	230 V

Operating current / Rated value	16 A
Appearance	
Color	grey
Product details	
Product component	
• Ejection equipment	No
• Labeling field	No
• Increased touch protection	No
• Fault current protection	No
• miniature fuse	No
• Integrated / functional lighting	No
• Integrated / Light source	No
• Integrated / orientation lighting	No
• Hinged lid	No
Product feature	
• lockable	No
• halogen-free	Yes
• transparent	No
Product function	
Product function	
• Socket selectable	No
• Overvoltage protection	No
Number	
Number of units	1
Number of sockets / switchable	0
Connections	
Arrangement of contacts / diagonal	No
Type of electrical connection	screw-type terminal
Mechanical Design	
Height	55.5 mm
Width	44 mm
Depth	75 mm
Material / of the enclosure	plastic
Ambient temperature	
• minimum	-10 °C
• maximum	55 °C



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TE6803>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/5TE6803/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TE6803**CAX-Online-Generator**<http://www.siemens.com/cax>**Tender specifications**<http://www.siemens.com/specifications>