

RS422 TO TTY CONVERTER, MALE (9-PIN) TO FEMALE (15-PIN),
FOR SCREW CONNECTION TO RS 422 INTERFACE, 180 DGR
CABLE OUTLET, FOR CONNECTION OF SIMATIC S5



General information	
Product type designation	Converter RS 422 to TTY
Installation type/mounting	
Wall mounting/direct mounting possible	Yes; Can be screwed onto the HMI
Interfaces	
HMI-side interface	
• Number of pins HMI-side	9; Pin (RS422)
Device-side interface	
• Number of pins device-side	15; Socket (TTY)
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-20 °C

• max.	70 °C
Relative humidity	
• Operation, max.	95 %
Mechanics/material	
Enclosure material (front)	
• Plastic	Yes
Screw type	
• 4.5 V	Yes; HMI page
Dimensions	
Width	42 mm
Height	62 mm
Thickness	11 mm
Weights	
Weight without packaging	28 g
Scope of supply	
Delivery quantity in pieces	1
Other	
Target devices	suitable for all SIMATIC HMI RS422 interfaces, for details refer to the operating instructions of the respective device
Usable in the following products	
• Product 1	6AV6642-0*
• Product 2	6AV6542-0*
• Product 3	6AV6545-0*
• Product 4	6AV6644-*
• Product 5	6AV6545-8*
• Product 6	6AV6640-0C*
• Product 7	6AV6643-7BA00-*
• Product 8	6AV6643-7CD00-*
• Product 9	6AV6643-7DD00-*
• Product 10	6av2124-0*
• Product 11	6av2124-1*
• Product 12	6AV2124-2*
• Product 13	6AV6647-0*
• Product 14	6AV6643-8*
• Product 15	6AV2123-2*
last modified:	10/28/2016