

SIPLUS ET 200SP, BASEUNIT BU15-P16+A10+2D, BU-TYPE A0, - 40 ... +70 DEGREES C WITH CONFORMAL COATING BASED ON 6ES7193-6BP20-0DA0 . PUSH-IN TERMINALS, WITH 10 AUX-TERMINALS, NEW LOADGROUP, WXH: 15MMX141MM



Figure similar

General information	
Product type designation	BU15-P16+A10+2D
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Current carrying capacity	
up to 60 °C, max.	10 A
Potential separation	
between backplane bus and supply voltage	Yes
Isolation	
Isolation tested with	707 V DC
Ambient conditions	
Extended ambient conditions	

- relative to ambient temperature-atmospheric pressure-installation altitude

Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)

Relative humidity

- With condensation, tested in accordance with IEC 60068-2-38, max.

100 %; RH incl. condensation/frost (no commissioning under condensation conditions)

Resistance

- against biologically active substances / conformity with EN 60721-3-3
- against chemically active substances / conformity with EN 60721-3-3
- against mechanically active substances / conformity with EN 60721-3-3

Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!

Yes; Class 3C4 (RH < 75%) incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!

Yes; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!

Dimensions

Width	15 mm
Height	141 mm
Depth	35 mm

Weights

Weight, approx.	50 g
-----------------	------

last modified: 10/28/2016