

N-ISOL. TERMINAL THERMOPLASTIC SCREW TERMINAL BLUE,
8MM, SZ 6




Figure similar

Model	
Busbar design	6x6 mm
General technical data	
Insulation material	thermoplastic
Terminal contact spacing	8 mm
Protection class	
Combustibility class acc. to UL 94	others
Main circuit	
Operating voltage / rated value	500 V
Operating current / rated value	41 A
Appearance	
Color	blue
Product details	
Product component / required / connection plate	No
Number	

Number of terminal points	1
---------------------------	---

Connections

Connectable conductor cross-section / stranded	
• minimum	6 mm ²
• maximum	6 mm ²
Wire stripping length	11 mm
Connectable conductor cross-section	
• solid	
— minimum	6 mm ²
— maximum	6 mm ²
• finely stranded	
— with core end processing / minimum	6 mm ²
— with core end processing / maximum	6 mm ²
— without core end processing / minimum	6 mm ²
— without core end processing / maximum	6 mm ²
Tightening torque / with screw-type terminals	
• minimum	0.8 N·m
• maximum	0.8 N·m
Type of electrical connection	screw-type terminals

Mechanical Design

Height / with lowest-profile installation	35 mm
Length	55 mm
Mounting type	others
Net weight	18 g
Material / of the insulating body	Thermoplast

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
--------------------------	---------------------------	-------------------	-------------------



[sonstig](#)



Shipping Approval	other
-------------------	-------



[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WA1011-1NH01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA1011-1NH01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1NH01

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>