

AS-INTERFACE M12 BRANCH AS-I W/O U-AUX,
CABLE, 2M, WITH M12 ANGLE PLUG IP 67/68/69K,
MAX. 6A



General technical data:

Type of device		AS-Interface accessories
Design of the product		AS-i M12 feeder, AS-i without Uaux, 2 m cable
Function		AS-i flat cable transition to M12
operating voltage according to AS-Interface specification	V	26.5 ... 31.6
Note		cable must not end in the feeder
Note 1		cable must not end in a feeder

Connections/ Terminals:

connection		insulation piercing method for AS-Interface flat cable
Connection system		insulation piercing method for AS-Interface flat cable
AS interface		
• Connection		M12 cable box 2 m

Inputs:

Inputs socket assignment		1 = AS-i "+" 3=AS-i "-"
--------------------------	--	-------------------------

Mechanical data:

Type of mounting		screw fixing
Contacts Load rating max	A	4

Ambient conditions:

ambient temperature	°C	-25 ... +75
ambient temperature when stored	°C	-25 ... +85
degree of protection		IP67/68/69K

Certificates/ approvals:

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity	Shipping Approval
--------------------------	---------------------------------------	---------------------------	-------------------



[sonstig](#)



Shipping Approval	other
-------------------	-------



[Umweltbestätigung](#)

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1901-1NR11>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1901-1NR11>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1901-1NR11&lang=en



last modified:

10/21/2016