

ABSOLUTE VALUE ENCODER 6FX2001-5SS24 MULTITURN 25 BIT WITH SSI, OPERAT. VOLT. 10-30 V STRIP FLANGE SHAFT 10MM AXIAL FLANGE SOCKET



Figure similar

product brand name	Measuring systems
Measuring procedure / for position feedback	absolute
Manner of function / of absolute encoder	multiturn
Operating voltage / of the rotary encoder / at DC	10 ... 30
Consumed current / typical	200 mA
Design of the interface	SSI
Design of input / for clock cycle	Differential line receiver according to EIA Standard RS 485
Design of encoder output	Differential line driver according to EIA Standard RS 485
Property of the output / Short-circuit proof	Yes
Clock frequency	100 kHz ... 1 MHz
Speed	
• for digital measuring accuracy +/- 1 bit / with electrical rotation transmission / maximum	5 000 1/min
• for digital measuring accuracy +/- 100 bit / with electrical rotation transmission / maximum	10 000 1/min
• maximum	10 000 1/min
Wire length	
• at 0 Hz ... 1 MHz / maximum	50 m

• at 0 Hz ... 300 kHz / maximum • at 0 Hz ... 100 kHz / maximum	100 m 400 m
Digital resolution	25 bit; (8192 increments x 4096 rpms)
Telegram length	25 bit; without parity
Type of coding • for sampling • for transmission	Gray Gray, fir-tree format
Product function • parameterizable preset • parameterizable counting direction	Yes; Set to zero Yes
Measurement deviation angle of rotation / of absolute encoder	79"; (with 8192 increments)
Friction torque / at 20 °C / maximum	0.01 N·m
Starting torque / at 20 °C / maximum	0.01 N·m
Axial force / at shaft • with $n > 6000$ rpm / maximum • with $n \leq 6000$ rpm / maximum	10 N 40 N
Cantilever force / at shaft extension • with $n > 6000$ rpm / maximum • with $n \leq 6000$ rpm / maximum	20 N 60 N
Rotary encoder shaft version	Solid shaft
Diameter / of rotary encoder shaft	10 mm
Length / of rotary encoder shaft	20 mm
Angular acceleration / maximum	100 000 rad/s ²
Moment of inertia / of rotor • with solid shaft encoder	0.0000015 kg·m ²
Vibrational acceleration / at 55 Hz ... 2 kHz / acc. to IEC 60068-2-6	300 m/s ²
Shock acceleration • limited to 2 ms / acc. to IEC 60068-2-27 • limited to 6 ms / acc. to IEC 60068-2-27	2 000 m/s ² 1 000 m/s ²
Protection class IP • without shaft input • with shaft input	IP67 IP64
Ambient temperature / during operation	-40 ... +85
EMI immunity	Tested to DIN EN 50081 and EN 50082
Certificate of suitability	CE, cULus
Type of electrical connection	Flange socket
Direction of connection opening	Axial
Flange type	Clamping flange
Net weight	0.35 kg

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Cataog/Product/6FX2001-5SS24/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6FX2001-5SS24/all>

last modified:

10/20/2016