

SWITCH, D=70MM 32A 3NC, TERMINAL 50QMM



Model	
product brandname	SENTRON
Product designation	Off switches
Type of light source	Not applicable
Mounting type / for light source	Not applicable
Design of the switching function	Off switches
General technical data	
Number of poles	3
Short-circuit current rating	10 kA
Type of voltage	AC
Protection class	
Protection class IP	Other
Switching capacity	
Switching capacity current / rated value	0.096 kA
Dissipation	
Power loss [W]	

- for rated value of the current / at AC / in hot operating state / per pole
- maximum

0.7 W

2.1 W

Main circuit

Operating voltage / rated value	400 V
Operating current / rated value	32 A

Appearance

Color / of the lens	Not applicable
---------------------	----------------

Product details

Product component / Signal lamp	No
---------------------------------	----

Product function

Product function / positive opening (acc. to DIN VDE 0113)	No
--	----

Number

Number of NC contacts	0
Number of NO contacts	3
Number of CO contacts	0

Mechanical Design

Installation depth	70 mm
Number of width units	3

**General Product
Approval**

Test Certificates

other



[Typprüfbescheinigung/W
erkszeugnis](#)

[sonstig](#)

[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TE8313>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5TE8313/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TE8313

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

