

CONTACTOR, AC-3, 30KW/400V DC 24V, 0.7...1.25*US, 3-POLE
SIZE S3, SCREW CONNECTION WITH SOLID-STATE CONTROL
BLOCK VARISTOR INTEGRATED



Figure similar

product brandname	SIRIUS
Product designation	power contactor
General technical data	
Size of contactor	S3
Insulation voltage	
• rated value	1 000 V
Degree of pollution	3
Surge voltage resistance rated value	6 kV
maximum permissible voltage for safe isolation	
• between coil and main contacts acc. to EN 60947-1	690 V
Protection class IP	
• on the front	IP00
• of the terminal	IP00
Shock resistance	
• at rectangular impulse	
— at DC	6,8g / 5 ms, 4g / 10 ms

• with sine pulse — at DC	10,6g / 5 ms, 6,2g / 10 ms
Mechanical service life (switching cycles)	
• of contactor typical	10 000 000
• of the contactor with added electronics-compatible auxiliary switch block typical	5 000 000
• of the contactor with added auxiliary switch block typical	10 000 000
Ambient conditions	
Installation altitude at height above sea level maximum	2 000 m
Ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-55 ... +80 °C
Main circuit	
Number of poles for main current circuit	3
Number of NO contacts for main contacts	3
Number of NC contacts for main contacts	0
Operating current	
• at AC-1 at 400 V — at ambient temperature 40 °C rated value	100 A
• at AC-1 — up to 690 V at ambient temperature 40 °C rated value — up to 690 V at ambient temperature 60 °C rated value — up to 1000 V at ambient temperature 40 °C rated value — up to 1000 V at ambient temperature 60 °C rated value	100 A 90 A 50 A 40 A
• at AC-3 — at 400 V rated value — at 690 V rated value — at 1000 V rated value	65 A 47 A 25 A
Connectable conductor cross-section in main circuit at AC-1	
• at 60 °C minimum permissible • at 40 °C minimum permissible	35 mm² 35 mm²
Operating current for approx. 200000 operating cycles at AC-4	
• at 400 V rated value • at 690 V rated value	28 A 20 A
Operating current	

• at 1 current path at DC-1 — at 24 V rated value — at 110 V rated value • with 2 current paths in series at DC-1 — at 24 V rated value — at 110 V rated value • with 3 current paths in series at DC-1 — at 24 V rated value — at 110 V rated value	90 A 4.5 A 90 A 90 A 90 A 90 A
Operating current • at 1 current path at DC-3 at DC-5 — at 24 V rated value — at 110 V rated value • with 2 current paths in series at DC-3 at DC-5 — at 110 V rated value — at 24 V rated value • with 3 current paths in series at DC-3 at DC-5 — at 110 V rated value — at 24 V rated value	40 A 2.5 A 90 A 90 A 90 A 90 A
Operating power • at AC-1 — at 230 V at 60 °C rated value — at 400 V rated value — at 690 V rated value — at 690 V at 60 °C rated value — at 1000 V at 60 °C rated value • at AC-2 at 400 V rated value • at AC-3 — at 230 V rated value — at 400 V rated value — at 500 V rated value — at 690 V rated value — at 1000 V rated value	34 kW 59 kW 102 kW 102 kW 66 W 30 kW 18.5 kW 30 kW 37 kW 45 kW 30 W
Operating power for approx. 200000 operating cycles at AC-4 • at 400 V rated value • at 690 V rated value	15.1 kW 18.6 kW
Thermal short-time current limited to 10 s	600 A
Power loss [W] at AC-3 at 400 V for rated value of the operating current per conductor	4.6 W
No-load switching frequency • at DC	1 000 1/h

Operating frequency	
• at AC-1 maximum	1 000 1/h
• at AC-2 maximum	400 1/h
• at AC-3 maximum	1 000 1/h
• at AC-4 maximum	300 1/h

Control circuit/ Control	
Type of voltage of the control supply voltage	DC
Control supply voltage at DC	
• rated value	24 V
Operating range factor control supply voltage rated value of magnet coil at DC	0.7 ... 1.25
Design of the surge suppressor	with varistor
Closing power of magnet coil at DC	19 W
Holding power of magnet coil at DC	12 W
Closing delay	
• at DC	90 ... 230 ms
Opening delay	
• at DC	14 ... 20 ms
Arcing time	10 ... 15 ms

Auxiliary circuit	
Number of NC contacts	
• for auxiliary contacts	
— instantaneous contact	0
Number of NO contacts	
• for auxiliary contacts	
— instantaneous contact	0
Operating current at AC-12 maximum	10 A
Operating current at AC-15	
• at 230 V rated value	6 A
• at 400 V rated value	3 A
Operating current at DC-12	
• at 60 V rated value	6 A
• at 110 V rated value	3 A
• at 220 V rated value	1 A
Operating current at DC-13	
• at 24 V rated value	10 A
• at 60 V rated value	2 A
• at 110 V rated value	1 A
• at 220 V rated value	0.3 A
Contact reliability of auxiliary contacts	1 faulty switching per 100 million (17 V, 1 mA)

UL/CSA ratings

Contact rating of auxiliary contacts according to UL	A600 / Q600
Short-circuit protection	
Design of the fuse link - for short-circuit protection of the main circuit - with type of coordination 1 required - with type of assignment 2 required - for short-circuit protection of the auxiliary switch required	fuse gL/gG: 250 A fuse gL/gG: 125 A fuse gL/gG: 10 A
Installation/ mounting/ dimensions	
Mounting type Side-by-side mounting	screw and snap-on mounting onto 35 mm and 75 mm standard mounting rail Yes
Height	176 mm
Width	70 mm
Depth	152 mm
Required spacing - for grounded parts - at the side	6 mm
Connections/Terminals	
Type of electrical connection - for main current circuit - for auxiliary and control current circuit	screw-type terminals screw-type terminals
Type of connectable conductor cross-sections - for main contacts - solid - stranded - single or multi-stranded - finely stranded with core end processing - finely stranded without core end processing - at AWG conductors for main contacts	2x (2.5 ... 16 mm ²) 2x (10 ... 50 mm ²) 2x (2,5 ... 16 mm ²) 2x (2.5 ... 35 mm ²) 2x (10 ... 35 mm ²) 2x (10 ... 1/0)
Type of connectable conductor cross-sections - for auxiliary contacts - solid - finely stranded with core end processing - at AWG conductors for auxiliary contacts	2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²), max. 2x (0.75 ... 4 mm ²) 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²) 2x (20 ... 16), 2x (18 ... 14), 1x 12
Certificates/approvals	

General Product Approval				Declaration of Conformity	Test Certificates
 CCC	 CSA	 UL		 EG-Konf.	spezielle Prüfbescheinigunge n

Test Certificates	Shipping Approval				other
Typprüfbescheinigung/Werkszeugnis	 ABS	 GL	 RINA	 RMRS	sonstig

other	
Umweltbestätigung	Bestätigungen

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT1044-1XB40-0LA2>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1044-1XB40-0LA2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1044-1XB40-0LA2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1044-1XB40-0LA2&lang=en



last modified:

10/31/2016