

FRONT CONN. MOD. (ANALOG 4X8E/A) S7-1500
FRONT CONNECTOR MODULE W. 4X16 POLE IDC-CONNECT.
FOR ANALOG 40 POL. I/O MODULES OF S7-1500 POTENTIAL
SUPPLY VIA INFEED ELEMENT



Operating data

Operating voltage	
• at DC / Rated value	24 V
• rated value	24 V
• at DC / maximum	60 V
Continuous current / at DC / per plug-in contact / maximum	1 A
Operating temperature	0 ... 60 °C
Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
Number of poles	40
number of the plug contacts / of the electrical connection	4
Type of electrical connection / for connecting cable	plug connector
Number of poles / at the 1st interface	16
Position / of the terminal	at the top
Width of screwdriver blade	3.5 mm
Product component / required / connection plate	No

Number of cables / per connection	2
Wire length / maximum	30 m

General data	
--------------	--

Mounting type	direct mounting
Degree of pollution	2
Overvoltage category	2
Design tested acc. to type of protection / EEx e	No
Certificate of suitability / cULus approval	Yes
Equipment marking / acc. to DIN EN 81346-2	X
Color / of the enclosure	black
Product feature / transparent	No
Net weight	0.099 kg

last modified: 10/20/2016