

SURGE SUPPRESSOR DIODE COMBINATION
(DIODE AND ZENER DIODE) DC 24 TO 250V SHORT
BREAKING TIME FOR PLUGGING ONTO
CONTACTORS WITHOUT/WITH AUX.CONTACT
BLOCKS



Figure similar

General technical data:		
Product designation		surge suppressor
Design of the surge suppressor		with diode assemblies
Control circuit/ Control:		
Type of voltage of the control supply voltage		DC
Control supply voltage 1		
• at DC		
— Initial rated value	V	24
— Final rated value	V	250
Certificates/ approvals:		

General Product Approval			Test Certificates	Shipping Approval	
			spezielle Prüfbescheinigungen n		

Shipping Approval	other		
	Bestätigungen	Umweltbestätigung	sonstig

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX4490-3B>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX4490-3B>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX4490-3B&lang=en

last modified:

10/07/2016