

CONTACTOR RELAY 44E EN 50 011 4NO+4NC, TAB
CONNECTOR WIDTH 45MM AC OPERATION AC 50HZ 110V/60HZ
132V

General technical data:

Size of contactor	0
Ambient temperature during operation	-25 ... +55 °C
Protection class IP on the front	IP00
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	K
Equipment marking acc. to DIN EN 81346-2	K

Control circuit/ Control:

Type of voltage of the control supply voltage	AC
Control supply voltage frequency	50 Hz 60 Hz
Control supply voltage	110 V 132 V
• at AC	
— at 50 Hz	
— rated value	
— at 60 Hz	
— rated value	

Auxiliary circuit:

Operating current at AC-15	4 A 3 A
• at 230 V rated value	
• at 400 V rated value	
Identification number and letter for switching elements	44 E
Number of NC contacts for auxiliary contacts	4
• lagging switching	0
• delayed switching	0
• make-before-break switching	0
Number of NO contacts for auxiliary contacts	4
• delayed switching	0
• leading contact	0
• make-before-break switching	0
Number of CO contacts for auxiliary contacts	0


Connections/ Terminals:

Type of electrical connection for auxiliary and control current circuit	tab terminals 2x 2.8 mm
---	-------------------------

Mechanical data:

Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Width	45 mm
Height	48 mm
Depth	96 mm

Certificates/approvals

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity
 CCC	 UL	 EG-Konf.
 CSA	 EAC	 Baumusterbescheinigung

Test Certificates	Shipping Approval	other
spezielle Prüfbescheinigungen	 GL	Umweltbestätigung
Typprüfbescheinigung/Werkszeugnis	 LRS	
sonstig		

other
Bestätigungen

Safety related data:

Protection against electrical shock	finger-safe
B10 value with high demand rate acc. to SN 31920	400 000
• Note	With 0.3 x I _e
T1 value for proof test interval or service life acc. to IEC 61508	20 y

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TH2244-1AF0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TH2244-1AF0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TH2244-1AF0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TH2244-1AF0&lang=en

last modified:

10/07/2016