



Figure similar

SIMATIC S7-1500, ANALOG OUTPUT MODULE AQ 8 X U/I HS 16
BITS OF RESOLUTION, ACCURACY 0.3 %, 8CHANNELS IN
GROUPS OF 8, DIAGNOSIS, SUBSTITUTE VALUE 8 CHANNELS
IN 0.125 MS INCL. INFEEED ELEMENT, SHIELD CLAMP AND
SHIELD TERMINAL

General information	
Product type designation	AQ 8xU/I HS
HW functional status	FS01
Firmware version	V2.1.0
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Output range scalable	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated as of version	V14 / -
• STEP 7 configurable/integrated as of version	V5.5 SP3 / -
• PROFIBUS as of GSD version/GSD revision	V1.0 / V5.1
• PROFINET as of GSD version/GSD revision	V2.3 / -
Operating mode	
• Oversampling	Yes
• MSO	Yes

CiR – Configuration in RUN

Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

Input current

Current consumption, max.	260 mA; with 24 V DC supply
---------------------------	-----------------------------

Power

Power available from the backplane bus	1.15 W
--	--------

Power loss

Power loss, typ.	7 W
------------------	-----

Analog outputs

Number of analog outputs	8
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	45 mA
Current output, no-load voltage, max.	20 V
Cycle time (all channels), min.	125 µs; independent of number of activated channels

Output ranges, voltage

• 0 to 10 V	Yes
• 1 V to 5 V	Yes
• -5 V to +5 V	No
• -10 V to +10 V	Yes

Output ranges, current

• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes

Connection of actuators

• for voltage output two-wire connection	Yes
• for voltage output four-wire connection	Yes
• for current output two-wire connection	Yes

Load impedance (in rated range of output)

• with voltage outputs, min.	1 kΩ
• with voltage outputs, capacitive load, max.	100 nF
• with current outputs, max.	500 Ω
• with current outputs, inductive load, max.	1 mH

Cable length

• shielded, max.	200 m
------------------	-------

Analog value generation for the outputs

Integration and conversion time/resolution per channel

- | | |
|--|--|
| • Resolution with overrange (bit including sign), max. | 16 bit |
| • Conversion time (per channel) | 50 µs; independent of number of activated channels |

Settling time

- | | |
|-----------------------|--|
| • for resistive load | 30 µs; see additional description in the manual |
| • for capacitive load | 100 µs; see additional description in the manual |
| • for inductive load | 100 µs; see additional description in the manual |

Errors/accuracies

Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	0.02 %
Linearity error (relative to output range), (+/-)	0.15 %
Temperature error (relative to output range), (+/-)	0.002 %/K
Crosstalk between the outputs, max.	-100 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.05 %

Operational error limit in overall temperature range

- | | |
|--|-------|
| • Voltage, relative to output range, (+/-) | 0.3 % |
| • Current, relative to output range, (+/-) | 0.3 % |

Basic error limit (operational limit at 25 °C)

- | | |
|--|-------|
| • Voltage, relative to output range, (+/-) | 0.2 % |
| • Current, relative to output range, (+/-) | 0.2 % |

Isochronous mode

Isochronous operation (application synchronized up to terminal)	Yes
Execution and activation time (TCO), min.	100 µs
Bus cycle time (TDP), min.	250 µs

Interrupts/diagnostics/status information

Diagnostics function	Yes
Substitute values connectable	Yes

Alarms

- | | |
|--------------------|-----|
| • Diagnostic alarm | Yes |
|--------------------|-----|

Diagnostic messages

- | | |
|---------------------------------|-------------------------------------|
| • Monitoring the supply voltage | Yes |
| • Wire-break | Yes; Only for output type "current" |
| • Short-circuit | Yes; Only for output type "voltage" |
| • Overflow/underflow | Yes |

Diagnostics indication LED

- | | |
|--|----------------|
| • RUN LED | Yes; Green LED |
| • ERROR LED | Yes; Red LED |
| • Monitoring of the supply voltage (PWR-LED) | Yes; Green LED |

- | | |
|---------------------------|----------------|
| • Channel status display | Yes; Green LED |
| • for channel diagnostics | Yes; Red LED |
| • for module diagnostics | Yes; Red LED |

Potential separation

Potential separation channels

- | | |
|--|-----|
| • between the channels | No |
| • between the channels, in groups of | 8 |
| • between the channels and backplane bus | Yes |
| • Between the channels and load voltage L+ | Yes |

Permissible potential difference

between S- and MANA (UCM)	8 V DC
---------------------------	--------

Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

Decentralized operation

Prioritized startup	No
---------------------	----

Dimensions

Width	35 mm
Height	147 mm
Depth	129 mm

Weights

Weight, approx.	325 g
-----------------	-------

last modified:	10/28/2016
-----------------------	------------