

DIGITAL TIME SWITCH MINI 1 CHANNEL WEEK 1 TE 120V TO 230 V



Model	
product brandname	SETRON
Product designation	Time-delay switch
Design of the product	Digital time switch Mini
Design of the switching function	CO contact
General technical data	
Manner of function	
• radio-controlled	No
• line-synchronous	No
• quartz-controlled	No
Accuracy / per day	0.3 s
Shortest switching time interval / of channel 1	1 s
Voltage	
Overvoltage category / acc. to IEC 61010-1	III
Supply voltage	
Supply voltage / initial value	230 V
Supply voltage / Full-scale value	230 V
Supply voltage frequency	

• minimum	50 Hz
• maximum	50 Hz
Type of voltage / of the supply voltage	AC
Protection class	
Protection class IP	IP20
Switching capacity	
Switching capacity current / at AC / at 250 V / Rated value	16 A
Dissipation	
Power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	0.035 W
Product details	
Product feature	
• external switch input	No
• floating switching contact	Yes
Product function	
Product function	
• 60 min time program	Yes
• Astro program	No
• Automatic daylight-saving adjustment	No
• Operating hours counter	No
• direct operation	Yes
• Holiday time program	No
• Impulse program	No
• annual time program	No
• Switching preselection	Yes
• 24-hour time program	Yes
• Text guidance in display	Yes
• Weekly time program	Yes
• Random time program	No
• Cyclical time program	No
Number	
Number of terminals / with cross-head screw	1
Number of channels	1
Number of memory slots	28
Connectable conductor cross-section / in main circuit	
• for rigid conductor / minimum	1.5 mm ²
• for rigid conductor / maximum	4 mm ²

- for flexible conductor / with core end processing / maximum

2.5 mm²

Mechanical Design

Height	83 mm
Width	18 mm
Depth	64 mm
Number of width units	1
Mounting type	DIN rail

Environmental conditions

Ambient temperature / minimum permissible	-10 °C
Ambient temperature	
• maximum permissible	55 °C
• during storage / minimum	-20 °C
• during storage / maximum	60 °C

Certificates

Equipment marking	
• acc. to DIN EN 61346-2	K
• acc. to DIN EN 81346-2	K

General Product Approval	Declaration of Conformity	other
---------------------------------	----------------------------------	--------------



[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/7LF4401-5>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/7LF4401-5/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7LF4401-5

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

