

Product type designation

IE FC RJ45 modular outlet (insert 2FE)
 INDUSTRIAL ETHERNET FASTCONNECT RJ45 MODULAR
 OUTLET,BASE MODULE WITH 2FE INSERT, REPL. INSERT FOR
 2 X 100 MBIT/S INTERFACE



Electrical data	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces	
Number of electrical connections	
• for Industrial Ethernet FC TP cables	1
• for network components or terminal equipment	2
Type of electrical connection	
• for Industrial Ethernet FC TP cables	integrated insulation displacement contacts
• for FC RJ45 modular outlet insert 2FE	2 x RJ45 socket (10/100 Mbit/s)
• FastConnect	Yes
Mechanical data	
Material / of the enclosure	metal
Design, dimensions and weight	
Width	50 mm
Height	115.25 mm
Depth	58.95 mm
Net weight	450 g

Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

Permitted ambient conditions

Ambient temperature	
• during operation	-20 ... +70 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP40

Standards, specifications, approvals

Certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
Standard for structured cabling	Cat 6

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 10/14/2016