

FUSE TERMINAL SCREW CONNECTION FOR G FUSE LINK
5X20MM AND 5X25MM WITH LED 24V



Figure similar

Model	
Type of light source / as fault indicator	LED
Design of the fuse link	glass fuse 5x25 mm
Design of fuse holder	pluggable
General technical data	
Insulation material	thermoplastic
Terminal contact spacing	10 mm
Supply voltage	
Type of voltage / for supply of the fault indicator	AC/DC
Protection class	
Combustibility class acc. to UL 94	Other
Main circuit	
Operating voltage / rated value	250 V
Operating current / rated value	6.3 A
Appearance	

Color	miscellaneous
-------	---------------

Product details

Product component / required / connection plate	No
---	----

Number

Number of terminal levels	1
---------------------------	---

Connections

Connectable conductor cross-section / stranded	
maximum	1.5 mm²
Connectable conductor cross-section	
- solid — minimum — maximum - finely stranded — with core end processing / minimum — with core end processing / maximum	1 mm² 1 mm² 0.75 mm² 1.5 mm²
Type of electrical connection	
1 2	screw-type terminal screw-type terminal
Position / of the terminal	lateral

Mechanical Design

Height / with lowest-profile installation	42 mm
Length	57 mm
Mounting type	DIN rail 35 mm
Material / of the insulating body	Thermoplast

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)
<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WA1011-1SF13>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<http://support.automation.siemens.com/WW/view/en/8WA1011-1SF13/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1SF13

CAX-Online-Generator
<http://www.siemens.com/cax>

